



## Equip 128382 USB4 Gen 2x2 C naar C-kabel, M/M, 2,0 m, PD 100W, 4K/60Hz, 20Gbps, Zwart



**Merk :** Equip

**Artikelcode:** 128382

**Productnaam :** 128382 USB4 Gen 2x2 C naar C-kabel, M/M, 2,0 m, PD 100W, 4K/60Hz, 20Gbps, Zwart

- "

- USB 4 Gen 2x2
- USB-C naar C Male
- 20Gbps gegevensoverdrachtsnelheid
- met E-mark chipset
- Power Delivery ondersteuning tot 20V/5A, Max. 100W
- Ondersteuning van USB Power Delivery (PD)
- Resolutie: tot 4K@60 Hz
- Ondersteunt HDR10
- Ondersteunt HDCP 1.4 en 2.3
- Ondersteunt PCI Express 3.0 protocol
- Ondersteunt DisplayPort 1.4a protocol
- Ondersteunt DP Alt Mode
- Compatibel met USB 3.2, USB 2.0 en Thunderbolt 3
- Omhulsel: Premium gevlochten katoenen gaas
- Dubbele afscherming voor foutloze gegevensoverdracht
- Aluminium behuizing"

USB4 Gen 2x2 C naar C-kabel, M/M, 2,0 m, PD 100W, 4K/60Hz, 20Gbps, Zwart

Equip 128382 USB4 Gen 2x2 C naar C-kabel, M/M, 2,0 m, PD 100W, 4K/60Hz, 20Gbps, Zwart.

Snoerlengte: 2 m. Aansluiting 1: USB C, Aansluiting 2: USB C, USB-versie: USB4 Gen 2x2, Max. overdrachtssnelheid: 20 Gbit/s, Kleur van het product: Zwart, Magnetisch afgeschermd

Features		Features	
USB version *	USB4 Gen 2x2	High Dynamic Range (HDR) supported	✓
Connector 1 *	USB C	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Connector 2 *	USB C	HDCP	✓
Connector 1 gender *	Male	HDCP version	1.4/2.3
Connector 2 gender *	Male	<b>Power</b>	
Connector 1 form factor	Straight	Input voltage	20 V
Connector 2 form factor	Straight	Input current (max)	5 A
Magnetically shielded	✓	<b>Weight &amp; dimensions</b>	
Cable jacket material	Cotton, Polyvinyl chloride (PVC)	Cable length *	2 m
Cable jacket type	Braided	Weight	85 g
Conductor material	Copper	<b>Packaging data</b>	
Connector housing material	Aluminum	Package type	Bag
Maximum data transfer rate	20000 Mbit/s	Package width	275 mm
Maximum data transfer rate	20 Gbit/s	Package depth	10 mm
Product colour *	Black	Package height	175 mm
Cable type	Round cable	Package weight	95 g
Plug and Play	✓	<b>Packaging content</b>	
USB Power Delivery (USB PD)	✓	Quantity per pack *	1 pc(s)
USB Power Delivery up to	100 W	<b>Certificates</b>	
USB Type-C DisplayPort Alternate Mode	✓	Compliance certificates	CE, RoHS
DisplayPort version	1.4a	<b>Logistics data</b>	
Maximum resolution	3840 x 2160 pixels	Country of origin	China
Maximum refresh rate	60 Hz		



4015867231067

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-FEB-2025. Prints or copies of Information are only valid on the printed Publication date