

ASUS ROG STRIX 1200W Gold Aura Edition power supply unit 20+4 pin ATX ATX Zwart

Merk : ASUS

Productfamilie: ROG

Artikelcode: 90YE00P0-B0NA00

Productnaam : ROG STRIX 1200W Gold Aura Edition



ASUS ROG STRIX 1200W Gold Aura Edition. Totaal vermogen: 1200 W, AC-ingangsspanning: 100 - 240 V, Gecombineerd vermogen (+3.3V): 120 W. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 60 cm, Lengte SATA-stroomkabel: 400,520,640 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 13,5 cm. Meegeleverde kabels: AC, CPU, PCIe, Peripheral (Molex), SATA



Energie		Poorten & interfaces	
Totaal vermogen *	1200 W	Lengte CPU-stroomkabel	65 cm
AC-ingangsspanning *	100 - 240 V	ATX power connector (20+4 pin)	✓
Gecombineerd vermogen (+3.3V)	120 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+12V)	1200 W	Prestatie	
Gecombineerd vermogen (+5V)	120 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (-12V)	3,6 W	Bedoeld voor *	PC
Gecombineerd vermogen(+5Vsb)	15 W	Vormfactor van de voeding (PSU) *	ATX
Max huidige output (+3.3V)	22 A	ATX version	3.0
Max huidige output(+12V)	100 A	Stille modus	✓
Max huidige output (+5V)	22 A	Bearing technologie	Kogellager
Max huidige output (-12V)	0,3 A	Design	
Max huidige output (+5Vsb)	3 A	Kleur van het product	Zwart
Efficiëntie	80 procent	Type koeling	Actief
Stroomspanning bescherming	Te hoog vermogen, Overspanning, Overbelasting, Oververhitting, Kortsluiting, Onder spanning	Ventilator diameter	13,5 cm
		Aantal ventilatoren	1 ventilator(en)
Poorten & interfaces		Belichting	✓
Motherboard power connector *	20+4 pin ATX	Aan/uitschakelaar	✓
Lengte stroomkabel moederbord	60 cm	Inhoud van de verpakking	
Aantal SATA power connectors	5	Meegeleverde kabels	AC, CPU, PCIe, Peripheral (Molex), SATA
Lengte SATA-stroomkabel	400,520,640 mm	Gewicht en omvang	
Peripheral (Molex) power connectors (4-pin) *	4	Breedte	180 mm
Lengte stroomkabel randapparaat (Molex)	150,300,400,550 mm	Diepte	150 mm
PCI Express power connectors (8-pin)	4	Hoogte	86 mm
PCI Express-voedingsconnectoren (16-pins)	1	Gewicht	3,23 kg
Lengte PCI Express-stroomkabel	70 cm	Verpakking	
CPU power connector (4+4 pin)	✓	Gebruikershandleiding	✓
		Breedte verpakking	386 mm
		Diepte verpakking	242 mm
		Hoogte verpakking	129 mm
		Gewicht verpakking	3,73 kg
		Type verpakking	Doos



4711081721475

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date