

Chieftec Polaris 3.0 1250W power supply unit 20+4 pin ATX ATX Zwart

Merk : Chieftec**Productfamilie:** Polaris**Artikelcode:** PPS-1250FC-A3**Productnaam :** POLARIS 3.0 1250W

Chieftec Polaris 3.0 1250W. Totaal vermogen: 1250 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 65 cm, Lengte SATA-stroomkabel: 100,550 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 13,5 cm. Breedte: 150 mm, Diepte: 160 mm, Hoogte: 86 mm



Energie		Poorten & interfaces	
Totaal vermogen *	1250 W	EPS power connector (8-pin)	✓
AC-ingangsspanning *	100 - 240 V	PCI Express power connectors (6+2 pin)	4
AC-ingangsfrequentie	50/60 Hz	PCI Express-voedingsconnectoren (16-pins)	1
Stroom	15-8 A	Bekabelingstype	Volledig modulair
Power factor	0,9	Prestatie	
Power Factor Correctie (PFC) type	Actief	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (+3.3V)	120 W	Bedoeld voor *	PC
Gecombineerd vermogen (+12V)	1250 W	Vormfactor van de voeding (PSU) *	ATX
Gecombineerd vermogen (+5V)	120 W	ATX version	3.0
Gecombineerd vermogen (-12V)	3,6 W	Bearing technologie	FDB
Gecombineerd vermogen(+5Vsb)	15 W	Design	
Max huidige output (+3.3V)	22 A	Kleur van het product	Zwart
Max huidige output(+12V)	104,1 A	Type koeling	Actief
Max huidige output (+5V)	22 A	Ventilator diameter	13,5 cm
Max huidige output (-12V)	0,3 A	Gewicht en omvang	
Max huidige output (+5Vsb)	3 A	Breedte	150 mm
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Kortsluiting, Onder spanning	Diepte	160 mm
Poorten & interfaces		Hoogte	86 mm
Motherboard power connector *	20+4 pin ATX	Gewicht	3,01 kg
Lengte stroomkabel moederbord	65 cm	Verpakking	
Aantal SATA power connectors	12	Gewicht verpakking	3,35 kg
Lengte SATA-stroomkabel	100,550 mm	Type verpakking	Doos
Peripheral (Molex) power connectors (4-pin) *	4	Technische details	
Lengte stroomkabel randapparaat (Molex)	100,550 mm	Naleving van duurzaamheid	✓
		Garantieperiode	5 jaar
		Certificaten van naleving	CB, CE, EAC, Federal Communications Commission (FCC), RoHS



0753263078155



753263078155

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date