



## APC Essential SurgeArrest 1 Outlet Black 230V Germany

PME1WB-GR

Call for More Information 31 (0) 23 5 124 124

- Basic Protection Against Power Surges for Computers and Electronics
- Includes: User Manual

| Output            |              |
|-------------------|--------------|
| Number of Outlets | 1.0          |
| Receptacle Style  | CEE 7 Schuko |

| Input                 |                  |
|-----------------------|------------------|
| Nominal Input Voltage | 220V, 230V, 240V |
| Input frequency       | 50/60 Hz         |
| Input Connections     | Schuko CEE 7/7P  |
| Input Power           | 4000.0Watts      |
| Maximum Input Current | 16.0A            |

| Surge Protection and Filtering |           |
|--------------------------------|-----------|
| Surge energy rating            | 680Joules |
| ts_nm_surge_response           | 1ns       |
| Peak Current Normal Mode       | 15kAmps   |

| Physical        |               |
|-----------------|---------------|
| Maximum Height  | 93MM, 9.32CM  |
| Maximum Width   | 63MM, 6.31CM  |
| Maximum Depth   | 40MM, 4.0CM   |
| Net Weight      | 0.05KG        |
| Shipping weight | 0.07KG        |
| Shipping Height | 100MM, 10.0CM |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.



| Physical   |                   |
|--|-------------------|
| Shipping Width                                     | 90MM, 9.0CM       |
| Shipping Depth                                     | 68MM, 6.8CM       |
| Color  | Black             |
| Master Carton Dimensions (Length x Width x Height) | 290 x 288 x 128MM |
| Master Carton Units                                | 12.0              |
| Master Carton Weight                               | 2.11              |
| Units per Pallet                                   | 1008.0            |
| SCC Codes  | 1073130434696 5   |

| Environmental               |               |
|-----------------------------|---------------|
| Operating Temperature       | 0 - 40 °C     |
| Operating Relative Humidity | 0 - 95 %      |
| Operating Elevation         | 0-3000meters  |
| Storage Temperature         | -15 - 45 °C   |
| Storage Relative Humidity   | 0 - 95 %      |
| Storage Elevation           | 0-15000meters |

| Conformance |             |
|-------------|-------------|
| Approvals   | CE, CE Mark |

| Sustainable Offer Status |                          |
|--------------------------|--------------------------|
| RoHS                     | Compliant                |
| REACH                    | REACH: Contains No SVHCs |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.