

TP-Link Omada ER706W draadloze router Gigabit Ethernet Dualband (2.4 GHz / 5 GHz) Zwart

Merk: TP-Link Productfamilie: Omada Artikelcode: ER706W

Productnaam: ER706W

TP-Link Omada ER706W. Type WAN-aansluiting: SFP. Wifi-band: Dual-band (2.4 GHz / 5 GHz), WLAN gegevensoverdrachtsnelheid (max): 3000 Mbit/s, WLAN gegevensoverdrachtsnelheid (eerste band): 574 Mbit/s. Interfacetype Ethernet LAN: Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s, Bekabelingstechnologie: 10/100/1000Base-T(X). Ondersteunde beveiligingsalgoritmen: WPA, WPA3-Enterprise. Routing protocols: OSPF, RIP






WAN connection		Security	
		,	
Ethernet WAN *	1	System event log	/
DSL WAN *	×	DMZ support	✓
SIM card slot *	×	Network address translation (NAT)	✓
3G/4G USB modem compatibility *	✓	Protocols	
WAN connection type	SFP	DHCP server	1
Wireless LAN features		Universal Plug and Play (UPnP)	1
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Routing protocols	OSPF, RIP
WLAN data transfer rate (max) * WLAN data transfer rate (first band)	3000 Mbit/s 574 Mbit/s	Design	
		Product colour	Black
WLAN data transfer rate (second band)	2402 Mbit/s	Wall mountable	✓
Network		LED indicators	System, USB, WAN, WLAN
Ethernet LAN *	,	Product type *	Desktop/pole router
Ethernet LAN interface type *	✓ Gigabit Ethernet	Certificates	
Ethernet LAN data rates	10,100,1000 Mbit/s	Certification	CE, FCC, RoHS
Cabling technology	10/100/1000 Mbig3 10/100/1000Base-T(X)	Packaging content	
Port forwarding	✓		
Port triggering	1	AC adapter included	1
Dynamic DNS (DDNS)	·	Manual	✓
VPN tunnels quantity	50	Antenna	
. ,		Antenna design *	External
Ports & interfaces		Antenna gain level (max)	4.5 dBi
Ethernet LAN (RJ-45) ports *	4	Antennas quantity	3
USB port *	✓	Features	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Internal memory	512 MB
DC-in jack	✓	Internal memory type	DDR4
		Flash memory	128 MB

Management features		Power	
Web-based management Reset button	<i>y</i>	Power source type * Output voltage Output current	DC 12 V 2 A
MU-MIMO technology MIMO	*	Operational conditions	
Security		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Security algorithms Guest access	WPA, WPA2, WPA3-Enterprise ✓	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 90%
Access Control List (ACL) Schedule access	1	Weight & dimensions	
Filtering	v	Width Depth	226 mm 131 mm
URL filtering	▼	Height	35 mm







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.