

LogiLink®



USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220

Portable designed for fast charging dual devices simultaneously,
perfect for traveling.



Best Connectivity



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220



4 052792 057089

Made in China

LogiLink®

USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220



Rapid Charging with PD3.0 and QC3.0

Charge your power-hungry devices with one USB-C PD port and one USB-A fast charging port.



Multiple Protection

Supports overcurrent, overvoltage, overheating and short circuit protections.

Best Connectivity



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220



4 052792 057089

Made in China

LogiLink®

USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220



Wide Compatibility

Compatible with most mobile devices: smartphones, tablets and much more.



Travel-Ready

Compact size easily fit in to laptop bag or backpack.

Best Connectivity



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220



4 052792 057089

Made in China

LogiLink®



USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220

Specification:

Input	100 - 240V AC 50/60Hz 1A max.
Output	USB-A port: 5V 3A (15W) / 9V 2A (18W) / 12V 1.5A (18W) USB-C port: 5V 3A (15W) / 9V 2A (18W) / 12V 1.5A (18W) *Max. Total Output 18W
Protections	Overcurrent, overvoltage, overheating and short circuit
Efficiency	Level V
Operating Temperature Range	0~40°C
Storage Temperature Range	-40°C ~ 85°C
Relative Humidity	25% ~ 90% (non-condensing)
Storage Humidity	10%~90% (non-condensing)
Dimension	89 x 51 x 29mm
Weight	62g



Package Contents:

- » 1 x USB Wall Charger
- » 1 x User Manual

Package Information:

- » Packing Dimension: 138 x 75 x 45mm
- » Packing Weight: 0.107kg
- » Carton Dimension: 465 x 315 x 167mm
- » Carton Q'ty: 40pcs
- » Carton Weight: 4.98kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



Made in China

Best Connectivity