

3.5 HDD DATA SHEET

## The Power of Agility for Creative Pro and SME NAS Enclosures



IronWolf™ Pro is designed for everything business NAS. Get used to tough, ready, and scalable 24x7 performance that can handle multi-drive environments across a wide range of capacities.



### Best-Fit Applications

- Commercial and enterprise network-attached storage (NAS)
- 1- to 24-bay network attached storage (NAS)
- Backup, archiving, and disaster recovery
- On-premise private cloud
- Virtual storage



## Key Advantages

**Optimized for NAS with AgileArray™.** AgileArray enables dual-plane balancing and RAID optimization in multi-bay environments, with the most advanced power management possible.

**Actively protect your NAS with IronWolf Health Management** focusing on prevention, intervention, and recovery.<sup>1</sup>

**High performance means no lag time** or downtime for users during workload traffic for the NAS. Seagate leads the competition with the highest-performing NAS drive portfolio.<sup>2</sup>

**Seagate® Rescue Data Recovery.<sup>3</sup>** IronWolf Pro comes with extra peace of mind for any mechanical, accidental, or natural disaster. With a 90% success rate of in-house recovery, Seagate has your back with a 2-year included Rescue Data Recovery plan.

**Rotational Vibration (RV) sensors.** First in its class of drives to include RV sensors to maintain high performance in multi-drive NAS enclosures.<sup>3</sup>

**Range of capacities up to 16TB.** More capacity options means more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

**Do more in multi-user environments.** IronWolf provides a workload rate of 300TB/year. Multiple users can confidently upload and download data to the NAS server, knowing IronWolf can handle the workload, whether you are a creative professional or a small business.

**Designed for always on, always accessible 24x7 performance.** Access data on your NAS any time, remotely or on site.

**1.2M hours MTBF, 5-year limited warranty** represents an improved total cost of ownership (TCO) over desktop drives with reduced maintenance costs.

<sup>1</sup> Contact your Seagate sales representative for further information.

<sup>2</sup> Performance may vary depending on user's hardware configuration and operating system.

<sup>3</sup> Registration required to activate. Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details.



| Specifications  | 16TB             | 14TB             | 12TB             | 10TB             | 8TB              |
|---|------------------|------------------|------------------|------------------|------------------|
| Capacity  | 16TB             | 14TB             | 12TB             | 10TB             | 8TB              |
| Standard Model Number <sup>1</sup>                      | ST16000NE000     | ST14000NE0008    | ST12000NE0008    | ST10000NE0008    | ST8000NE001      |
| Interface   | SATA 6Gb/s       | SATA 6Gb/s       | SATA 6Gb/s       | SATA 6Gb/s       | SATA 6Gb/s       |
| <b>Features</b>   |                  |                  |                  |                  |                  |
| Drive Bays Supported                                    | Up to 24-bay     | Up to 24-bay     | Up to 24-bay     | Up to 24-bay     | Up to 24-bay     |
| Multi-User Technology (TB/yr)                           | 300              | 300              | 300              | 300              | 300              |
| Rotational Vibration (RV) Sensors                       | Yes              | Yes              | Yes              | Yes              | Yes              |
| Hot-Plug Support <sup>2</sup>                           | Yes              | Yes              | Yes              | Yes              | Yes              |
| Cache (MB)  | 256              | 256              | 256              | 256              | 256              |
| <b>Reliability/Data Integrity</b>                       |                  |                  |                  |                  |                  |
| Mean Time Between Failures (MTBF, hours)                | 1,200,000        | 1,200,000        | 1,200,000        | 1,200,000        | 1,200,000        |
| Reliability Rating @ Full 24x7 Operation (AFR)          | 0.73%            | 0.73%            | 0.73%            | 0.73%            | 0.73%            |
| Nonrecoverable Read Errors per Bits Read, Max           | 1 per 10E15      | 1 per 10E15      | 1 per 10E15      | 1 per 10E15      | 1 per 10E15      |
| Power-On Hours per Year (24x7)                          | 8760             | 8760             | 8760             | 8760             | 8760             |
| Sector Size (Bytes per Logical Sector)                  | 512E             | 512E             | 512E             | 512E             | 512E             |
| Rescue Services <sup>3</sup>                            | Yes              | Yes              | Yes              | Yes              | Yes              |
| Limited Warranty (years)                                | 5                | 5                | 5                | 5                | 5                |
| <b>Performance</b>                                      |                  |                  |                  |                  |                  |
| Spindle Speed (RPM)                                     | 7200             | 7200             | 7200             | 7200             | 7200             |
| Interface Access Speed (Gb/s)                           | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    |
| Max. Sustained Transfer Rate OD (MB/s)                  | 250MB/s          | 250MB/s          | 250MB/s          | 240MB/s          | 240MB/s          |
| Average Latency (ms)                                    | 4.16             | 4.16             | 4.16             | 4.16             | 4.16             |
| Interface Ports   | Single           | Single           | Single           | Single           | Single           |
| Rotational Vibration @ 10-1500 Hz (rad/s <sup>2</sup> ) | 12.5             | 12.5             | 12.5             | 12.5             | 12.5             |
| <b>Power Consumption</b>                                |                  |                  |                  |                  |                  |
| Startup Current, Typical (12V, A)                       | 2.0              | 2.0              | 2.0              | 2.0              | 2.0              |
| Idle Power, Average (W)                                 | 5.0              | 5.0              | 5.0              | 5.0              | 7.06             |
| Average Operating Power (W)                             | 7.6W             | 7.6W             | 7.8W             | 7.8W             | 9.2W             |
| Standby Mode (W)  | 1.0              | 1.0              | 1.0              | 0.8              | 1.0              |
| Sleep Mode (W)  | 1.0              | 1.0              | 1.0              | 0.8              | 1.0              |
| Power Supply Requirements                               | +12 V and +5 V   | +12 V and +5 V   | +12 V and +5 V   | +12 V and +5 V   | +12 V and +5 V   |
| <b>Environmental/Temperature</b>                        |                  |                  |                  |                  |                  |
| Operating (ambient, min °C)                             | 5                | 5                | 5                | 5                | 5                |
| Operating (drive case, max °C)                          | 60               | 60               | 60               | 60               | 60               |
| Nonoperating (ambient, min °C)                          | -40              | -40              | -40              | -40              | -40              |
| Nonoperating (ambient, max °C)                          | 70               | 70               | 70               | 70               | 70               |
| <b>Environmental/Acoustics</b>                          |                  |                  |                  |                  |                  |
| Vibration, Nonoperating: 10Hz to 500Hz (Grms)           | 2.27             | 2.27             | 2.27             | 2.27             | 2.27             |
| Idle (typical) <sup>3</sup>                             | 2.8bels          | 2.8bels          | 2.8bels          | 2.8bels          | 1.8bels          |
| Seek (typical)  | 3.2bels          | 3.2bels          | 3.2bels          | 3bels            | 2.8bels          |
| <b>Environmental/Shock</b>                              |                  |                  |                  |                  |                  |
| Shock, Operating 2ms (Read/Write) (Gs)                  | 50/50Gs          | 50/50Gs          | 50/50Gs          | 70/40Gs          | 70/40Gs          |
| Shock, Nonoperating, 1ms and 2ms (Gs)                   | 200              | 200              | 200              | 250              | 250              |
| <b>Physical</b>   |                  |                  |                  |                  |                  |
| Height (mm/in)  | 26.11mm/1.028in  | 26.11mm/1.028in  | 26.11mm/1.028in  | 26.11mm/1.028in  | 26.11mm/1.028in  |
| Width (mm/in, max)                                      | 101.85mm/4.01in  | 101.85mm/4.01in  | 101.85mm/4.01in  | 101.85mm/4.01in  | 101.85mm/4.01in  |
| Depth (mm/in, max)                                      | 146.99mm/5.787in | 146.99mm/5.787in | 146.99mm/5.787in | 146.99mm/5.787in | 146.99mm/5.787in |
| Weight (g/lb)   | 670g/1.477lb     | 670g/1.477lb     | 670g/1.477lb     | 690g/1.521lb     | 722g/1.59lb      |
| Carton Unit Quantity                                    | 20               | 20               | 20               | 20               | 20               |
| Cartons per Pallet/Cartons per Layer                    | 40/8             | 40/8             | 40/8             | 40/8             | 40/8             |

<sup>1</sup> Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

<sup>2</sup> Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.





| Specifications  | 8TB              | 6TB              | 6TB              | 4TB              | 4TB              |
|---|------------------|------------------|------------------|------------------|------------------|
| Capacity  | 8TB              | 6TB              | 6TB              | 4TB              | 4TB              |
| Standard Model Number <sup>1</sup>                      | ST8000NE0021     | ST6000NE000      | ST6000NE0023     | ST4000NE001      | ST4000NE0025     |
| Interface   | SATA 6Gb/s       | SATA 6Gb/s       | SATA 6Gb/s       | SATA 6Gb/s       | SATA 6Gb/s       |
| <b>Features</b>   |                  |                  |                  |                  |                  |
| Drive Bays Supported                                    | Up to 24-bay     | Up to 24-bay     | Up to 24-bay     | Up to 24-bay     | Up to 24-bay     |
| Multi-User Technology (TB/yr)                           | 300              | 300              | 300              | 300              | 300              |
| Rotational Vibration (RV) Sensors                       | Yes              | Yes              | Yes              | Yes              | Yes              |
| Hot-Plug Support <sup>2</sup>                           | Yes              | Yes              | Yes              | Yes              | Yes              |
| Cache (MB)  | 256              | 256              | 256              | 128              | 128              |
| <b>Reliability/Data Integrity</b>                       |                  |                  |                  |                  |                  |
| Mean Time Between Failures (MTBF, hours)                | 1,200,000        | 1,200,000        | 1,200,000        | 1,200,000        | 1,200,000        |
| Reliability Rating @ Full 24x7 Operation (AFR)          | 0.73%            | 0.73%            | 0.73%            | 0.73%            | 0.73%            |
| Nonrecoverable Read Errors per Bits Read, Max           | 1 per 10E15      | 1 per 10E15      | 1 per 10E15      | 1 per 10E15      | 1 per 10E15      |
| Power-On Hours per Year (24x7)                          | 8760             | 8760             | 8760             | 8760             | 8760             |
| Sector Size (Bytes per Logical Sector)                  | 512E             | 512E             | 512E             | 512E             | 512E             |
| Rescue Services <sup>3</sup>                            | Yes              | Yes              | Yes              | Yes              | Yes              |
| Limited Warranty (years)                                | 5                | 5                | 5                | 5                | 5                |
| <b>Performance</b>                                      |                  |                  |                  |                  |                  |
| Spindle Speed (RPM)                                     | 7200             | 7200             | 7200             | 7200             | 7200             |
| Interface Access Speed (Gb/s)                           | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    |
| Max. Sustained Transfer Rate OD (MB/s)                  | 240MB/s          | 220MB/s          | 220MB/s          | 220MB/s          | 220MB/s          |
| Average Latency (ms)                                    | 4.16             | 4.16             | 4.16             | 4.16             | 4.16             |
| Interface Ports   | Single           | Single           | Single           | Single           | Single           |
| Rotational Vibration @ 10-1500 Hz (rad/s <sup>2</sup> ) | 12.5             | 12.5             | 12.5             | 12.5             | 12.5             |
| <b>Power Consumption</b>                                |                  |                  |                  |                  |                  |
| Startup Current, Typical (12V, A)                       | 2.0              | 2.0              | 2.0              | 2.0              | 2.0              |
| Idle Power, Average (W)                                 | 8.63             | 7.06             | 7.5              | 5.5              | 5.45             |
| Average Operating Power (W)                             | 8.78W            | 8.1W             | 8.1W             | 9.0W             | 8.5W             |
| Standby Mode (W)  | 0.8              | 1.0              | 0.6              | 1.0              | 0.6              |
| Sleep Mode (W)  | 0.8              | 1.0              | 0.6              | 1.0              | 0.6              |
| Power Supply Requirements                               | +12 V and +5 V   | +12 V and +5 V   | +12 V and +5 V   | +12 V and +5 V   | +12 V and +5 V   |
| <b>Environmental/Temperature</b>                        |                  |                  |                  |                  |                  |
| Operating (ambient, min °C)                             | 5                | 5                | 5                | 5                | 5                |
| Operating (drive case, max °C)                          | 60               | 60               | 60               | 60               | 60               |
| Nonoperating (ambient, min °C)                          | -40              | -40              | -40              | -40              | -40              |
| Nonoperating (ambient, max °C)                          | 70               | 70               | 70               | 70               | 70               |
| <b>Environmental/Acoustics</b>                          |                  |                  |                  |                  |                  |
| Vibration, Nonoperating: 10Hz to 500Hz (Grms)           | 2.27             | 3                | 3                | 3                | 3                |
| Idle (typical) <sup>3</sup>                             | 1.8bels          | 2.7bels          | 2.7bels          | 2.7bels          | 2.7bels          |
| Seek (typical)  | 2.8bels          | 2.7bels          | 2.7bels          | 2.8bels          | 2.8bels          |
| <b>Environmental/Shock</b>                              |                  |                  |                  |                  |                  |
| Shock, Operating 2ms (Read/Write) (Gs)                  | 70/40Gs          | 70/40Gs          | 70/40Gs          | 70/40Gs          | 70/40Gs          |
| Shock, Nonoperating, 1ms and 2ms (Gs)                   | 250              | 250              | 250              | 300              | 300              |
| <b>Physical</b>   |                  |                  |                  |                  |                  |
| Height (mm/in)  | 26.11mm/1.028in  | 26.11mm/1.028in  | 26.11mm/1.028in  | 26.11mm/1.028in  | 26.11mm/1.028in  |
| Width (mm/in, max)                                      | 101.85mm/4.01in  | 101.85mm/4.01in  | 101.85mm/4.01in  | 101.85mm/4.01in  | 101.85mm/4.01in  |
| Depth (mm/in, max)                                      | 146.99mm/5.787in | 146.99mm/5.787in | 146.99mm/5.787in | 146.99mm/5.787in | 146.99mm/5.787in |
| Weight (g/lb)   | 780g/1.72lb      | 705g/1.55lb      | 705g/1.55lb      | 643g/1.42lb      | 680g/1.50lb      |
| Carton Unit Quantity                                    | 20               | 20               | 20               | 20               | 20               |
| Cartons per Pallet/Cartons per Layer                    | 40/8             | 40/8             | 40/8             | 40/8             | 40/8             |

<sup>1</sup> Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

<sup>2</sup> Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.





| Specifications  | 2TB              | 2TB              |
|---|------------------|------------------|
| Capacity  | 2TB              | 2TB              |
| Standard Model Number <sup>1</sup>                      | ST2000NE0025     | ST2000NE001      |
| Interface   | SATA 6Gb/s       | SATA 6Gb/s       |
| <b>Features</b>   |                  |                  |
| Drive Bays Supported                                    | Up to 24-bay     | Up to 24-bay     |
| Multi-User Technology (TB/yr)                           | 300              | 300              |
| Rotational Vibration (RV) Sensors                       | Yes              | Yes              |
| Hot-Plug Support <sup>2</sup>                           | Yes              | Yes              |
| Cache (MB)  | 128              | 256              |
| <b>Reliability/Data Integrity</b>                       |                  |                  |
| Mean Time Between Failures (MTBF, hours)                | 1,200,000        | 1,200,000        |
| Reliability Rating @ Full 24x7 Operation (AFR)          | 0.73%            | 0.73%            |
| Nonrecoverable Read Errors per Bits Read, Max           | 1 per 10E15      | 1 per 10E15      |
| Power-On Hours per Year (24x7)                          | 8760             | 8760             |
| Sector Size (Bytes per Logical Sector)                  | 512              | 512              |
| Rescue Services <sup>3</sup>                            | Yes              | Yes              |
| Limited Warranty (years)                                | 5                | 5                |
| <b>Performance</b>                                      |                  |                  |
| Spindle Speed (RPM)                                     | 7200             | 7200             |
| Interface Access Speed (Gb/s)                           | 6.0, 3.0, 1.5    | 6.0, 3.0, 1.5    |
| Max. Sustained Transfer Rate OD (MB/s)                  | 195MB/s          | 195MB/s          |
| Average Latency (ms)                                    | 4.16             | 4.16             |
| Interface Ports   | Single           | Single           |
| Rotational Vibration @ 10-1500 Hz (rad/s <sup>2</sup> ) | 12.5             | 12.5             |
| <b>Power Consumption</b>                                |                  |                  |
| Startup Current, Typical (12V, A)                       | 2.0              | 2.0              |
| Idle Power, Average (W)                                 | 4.61             | 4.61             |
| Average Operating Power (W)                             | 6.5W             | 7.1W             |
| Standby Mode (W)  | 0.8              | 1.0              |
| Sleep Mode (W)  | 0.8              | 1.0              |
| Power Supply Requirements                               | +12 V and +5 V   | +12 V and +5 V   |
| <b>Environmental/Temperature</b>                        |                  |                  |
| Operating (ambient, min °C)                             | 5                | 5                |
| Operating (drive case, max °C)                          | 60               | 60               |
| Nonoperating (ambient, min °C)                          | -40              | -40              |
| Nonoperating (ambient, max °C)                          | 70               | 70               |
| <b>Environmental/Acoustics</b>                          |                  |                  |
| Vibration, Nonoperating: 10Hz to 500Hz (Grms)           | 3                | 3                |
| Idle (typical) <sup>3</sup>                             | 2.2bels          | 2.8bels          |
| Seek (typical)  | 2.6bels          | 3.2bels          |
| <b>Environmental/Shock</b>                              |                  |                  |
| Shock, Operating 2ms (Read/Write) (Gs)                  | 70/40Gs          | 70/40Gs          |
| Shock, Nonoperating, 1ms and 2ms (Gs)                   | 300              | 300              |
| <b>Physical</b>   |                  |                  |
| Height (mm/in)  | 26.11mm/1.028in  | 26.11mm/1.028in  |
| Width (mm/in, max)                                      | 101.85mm/4.01in  | 101.85mm/4.01in  |
| Depth (mm/in, max)                                      | 146.99mm/5.787in | 146.99mm/5.787in |
| Weight (g/lb)   | 550g/1.21lb      | 620g/1.37lb      |
| Carton Unit Quantity                                    | 20               | 20               |
| Cartons per Pallet/Cartons per Layer                    | 40/8             | 40/8             |

<sup>1</sup> Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

<sup>2</sup> Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.

**seagate.com**



© 2019 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications.  
DS1914.11A-1909US September 2019