

ASUS ROG STRIX 1000W Gold (16-pin cable) power supply unit 20+4 pin ATX ATX Zwart

Merk : ASUS

Artikelcode: 90YE00AA-B0NA00

Productnaam : ROG STRIX 1000W Gold (16-pin cable)

ASUS ROG STRIX 1000W Gold (16-pin cable). Totaal vermogen: 1000 W, AC-ingangsspanning: 100 - 240 V, Gecombineerd vermogen (+3.3V): 125 W. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 61 cm, Lengte SATA-stroomkabel: 400,120,410,150 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 13,5 cm. Meegeleverde kabels: CPU, PCIe, SATA, Peripheral (Molex)



Energie		Poorten & interfaces	
Totaal vermogen *	1000 W	CPU power connector (4+4 pin)	✓
AC-ingangsspanning *	100 - 240 V	Lengte CPU-stroomkabel	100 cm
Gecombineerd vermogen (+3.3V)	125 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+12V)	996 W	Prestatie	
Gecombineerd vermogen (+5V)	125 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (-12V)	3,6 W	Bedoeld voor *	PC
Gecombineerd vermogen(+5Vsb)	15 W	Vormfactor van de voeding (PSU) *	ATX
Max huidige output (+3.3V)	25 A	Stille modus	✓
Max huidige output(+12V)	83 A	Bearing technologie	DBB
Max huidige output (+5V)	25 A	Design	
Max huidige output (-12V)	0,3 A	Kleur van het product	Zwart
Max huidige output (+5Vsb)	3 A	Type koeling	Actief
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning	Ventilator diameter	13,5 cm
Poorten & interfaces		Aantal ventilatoren	1 ventilator(en)
Motherboard power connector *	20+4 pin ATX	Ventilator locatie	Boven
Lengte stroomkabel moederbord	61 cm	Belichting	✓
Aantal SATA power connectors	8	Inhoud van de verpakking	
Lengte SATA-stroomkabel	400,120,410,150 mm	Meegeleverde kabels	CPU, PCIe, SATA, Peripheral (Molex)
Peripheral (Molex) power connectors (4-pin) *	4	Gewicht en omvang	
Lengte stroomkabel randapparaat (Molex)	450,120 mm	Breedte	160 mm
PCI Express power connectors (6+2 pin)	3	Diepte	150 mm
PCI Express-voedingsconnectoren (16-pins)	1	Hoogte	86 mm
Lengte PCI Express-stroomkabel	67,5 cm	Gewicht	1,88 kg
		Verpakking	
		Breedte verpakking	310 mm
		Diepte verpakking	180 mm
		Hoogte verpakking	115 mm

Verpakking

Gewicht verpakking	3,54 kg
Type verpakking	Doos

Technische details

Certificaten van naleving	RoHS
---------------------------	------



4711387246115

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date