

StarTech.com 136B-USBC-HDMI213M video kabel adapter 3 m USB Type-C HDMI Type A (Standaard) Grijs

Merk : StarTech.com

Artikelcode: 136B-USBC-HDMI213M

Productnaam : 136B-USBC-HDMI213M

StarTech.com 3m USB-C naar HDMI Adapter Kabel, 8K 60Hz, 4K 144Hz, HDR10, USB Type-C naar HDMI 2.1 Video Converter Kabel, USB-C DP Alt Mode/USB4/Thunderbolt 3/4 Compatibel (136B-USBC-HDMI213M)

StarTech.com 136B-USBC-HDMI213M video kabel adapter 3 m USB Type-C HDMI Type A (Standaard) Grijs:

Sluit een USB-C bron met DP Alt Mode aan op een HDMI-monitor tot op 3m afstand, met ondersteuning voor HDR-video en resoluties tot 8K 60Hz

The StarTech.com Advantage

StarTech.com 136B-USBC-HDMI213M. Snoerlengte: 3 m, Aansluiting 1: USB Type-C, Aansluiting 2: HDMI Type A (Standaard). Diameter van de kabel: 4,8 mm. Aantal per verpakking: 1 stuk(s), Breedte verpakking: 149 mm, Diepte verpakking: 213 mm. (Buitenste) hoofdverpakking breedte: 473 mm, (Buitenste) hoofdverpakking lengte: 331 mm, (Buitenste) hoofdverpakking hoogte: 440 mm



Kenmerken		Eisen aan de omgeving	
Connector 1 vormfactor	Recht	Bedrijfstemperatuur (T-T)	0 - 40 °C
Connector 2 vormfactor	Recht	Temperatuur bij opslag	-40 - 75 °C
Snoerlengte *	3 m	Relatieve vochtigheid in bedrijf (V-V)	0 - 80 procent
Aansluiting 1 *	USB Type-C	Duurzaamheid	
Aansluiting 2 *	HDMI Type A (Standaard)	Naleving van duurzaamheid	✓
Aansluiting 1 type *	Mannelijk	Gewicht en omvang	
Aansluiting 2 type *	Mannelijk	Diameter van de kabel	4,8 mm
HDMI versie	2.1	Verpakking	
HDCP	✓	Aantal per verpakking	1 stuk(s)
HDCP versie	1.4/2.2/2.3	Breedte verpakking	149 mm
USB Type-C DisplayPort alternatieve modus	✓	Diepte verpakking	213 mm
HDR-ondersteuning	✓	Hoogte verpakking	51 mm
Maximum resolutie	7680 x 4320 Pixels	Gewicht verpakking	207,8 g
Ondersteunde grafische resoluties	1920 x 1080 (HD 1080), 2560 x 1440, 3840 x 2160, 5120 x 1440, 7680 x 4320	Technische details	
Kleur van het product	Grijs	Certificaten van naleving	CE, RoHS
Chipset	VMM7100	Logistieke gegevens	
Materiaal buitenmantel	Polyvinyl chloride (PVC)	(Buitenste) hoofdverpakking breedte	473 mm
Ondersteunde audiokanalen	7.1	(Buitenste) hoofdverpakking lengte	331 mm
High Dynamic Range (HDR)-technologie	High Dynamic Range 10 (HDR10)	(Buitenste) hoofdverpakking hoogte	440 mm
Dolby technologieën	DTS:X, Dolby Atmos	Hoeveelheid per (buitenste) hoofdverpakking	32 stuk(s)



0065030897433



065030897433

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date