

Chieftec Smart 300W power supply unit 20+4 pin ATX TFX Grijs

Merk : Chieftec

Artikelcode: GPF-300P

Productnaam : Smart 300W

Chieftec Smart 300W. Totaal vermogen: 300 W, AC-ingangsspanning: 115 - 230 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 30 cm, Lengte SATA-stroomkabel: 150,350 mm. Bedoeld voor: Pc/server, Vormfactor van de voeding (PSU): TFX, 80 PLUS certificatie: 80 PLUS Bronze. Kleur van het product: Grijs, Type koeling: Actief, Ventilator diameter: 8 cm. Breedte: 85 mm, Diepte: 175 mm, Hoogte: 65 mm



Energie		Poorten & interfaces	
Totaal vermogen *	300 W	EPS-voedingsconnector (4+4 pin)	✓
AC-ingangsspanning *	115 - 230 V	Lengte CPU-stroomkabel	35 cm
AC-ingangsfrequentie	47 - 63 Hz	Floppy drive power connector	1
Stroom	6.3 A	Lengte kabel diskettestation	15 cm
Power factor	0,9	Bekabelingstype	Niet-modulair
Power Factor Correctie (PFC) type	Actief	Prestatie	
Gecombineerd vermogen (+3.3V)	95 W	80 PLUS certificatie *	80 PLUS Bronze
Gecombineerd vermogen (+5V)	95 W	Bedoeld voor *	Pc/server
Gecombineerd vermogen (-12V)	3,6 W	Vormfactor van de voeding (PSU) *	TFX
Gecombineerd vermogen(+5Vsb)	10 W	ATX version	2.3
Max huidige output (+3.3V)	16 A	Design	
Max output current (+12V1)	14 A	Kleur van het product	Grijs
Max output current (+12V2)	15 A	Type koeling	Actief
Max huidige output (+5V)	15 A	Ventilator diameter	8 cm
Max huidige output (-12V)	0,3 A	Aantal ventilatoren	1 ventilator(en)
Max huidige output (+5Vsb)	2 A	Gewicht en omvang	
Stroomspanning bescherming	Overspanning, Oververhitting, Overbelasting, Kortsluiting, Onder spanning	Breedte	85 mm
Poorten & interfaces		Diepte	175 mm
Motherboard power connector *	20+4 pin ATX	Hoogte	65 mm
Lengte stroomkabel moederbord	30 cm	Gewicht	1,07 kg
Aantal SATA power connectors	4	Verpakking	
Lengte SATA-stroomkabel	150,350 mm	Gewicht verpakking	1,13 kg
Peripheral (Molex) power connectors (4-pin) *	2	Technische details	
Lengte stroomkabel randapparaat (Molex)	150,350 mm	Certificaten van naleving	RoHS
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 84733020	



4710713234666



5715063383896

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date