



TP-Link Deco X1500 Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Wit 2 Intern

Merk : TP-Link

Artikelcode: DECO X1500(3-PACK)

Productnaam : Deco X1500

TP-Link Deco X1500. Kleur van het product: Wit, Soort antenne: Intern, Type product: Mesh-systeem. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 6 (802.11ax), WLAN gegevensoverdrachtsnelheid (max): 1500 Mbit/s. Functies voor ouderlijk toezicht: Bedtijd, Aangepaste profielen, Tijd met familie, Off time, Professional content filter library,.... Certificering: CE, FCC, RoHS, JPA, JRF, VCCI, NCC, BSMI. Breedte: 110 mm, Diepte: 110 mm, Hoogte: 114 mm



Design		Wireless LAN features	
Product type	Mesh system	Guest access	✓
Product colour *	White	Apps supported	TP-Link Deco
LED indicators	Power	Features	
Antenna type *	Internal	Quality of Service (QoS) support	✓
Reset button	✓	Port forwarding	✓
Wireless LAN features		BeamForming	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Parental control	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Parental control features	Bedtime, Custom profiles, Family time, Off time, Professional content filter library, Time rewards
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	MU-MIMO technology	✓
WLAN data transfer rate (max) *	1500 Mbit/s	MIMO	✓
WLAN data transfer rate (first band)	300 Mbit/s	Ports & interfaces	
WLAN data transfer rate (second band)	1201 Mbit/s	Ethernet LAN (RJ-45) ports *	2
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	DC-in jack	✓
Security algorithms	WPA-Personal, WPA2-Personal, WPA3	Certificates	
Number of guest networks (5 GHz)	1	Certification	CE, FCC, RoHS, JPA, JRF, VCCI, NCC, BSMI
Number of guest networks (2.4 GHz)	1	Operational conditions	
Point-to-point protocol over Ethernet (PPPoE)	✓	Operating temperature (T-T)	0 - 40 °C
Dynamic IP	✓	Storage temperature (T-T)	-40 - 60 °C
Static IP	✓	Operating relative humidity (H-H)	10 - 90%
Wireless Distribution System (WDS) bridge	✓	Storage relative humidity (H-H)	5 - 90%
IGMP proxy	✓	Weight & dimensions	
IGMP snooping	✓	Width	110 mm
Tagged VLAN	✓	Depth	110 mm
Dynamic DNS (DDNS)	✓	Height	114 mm
		Packaging content	
		AC adapter included	✓
		Number of units included	3 pc(s)
		Ethernet cable	✓
		Quick installation guide	✓



4895252505092



4895252505085

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-FEB-2025. Prints or copies of Information are only valid on the printed Publication date