

NETGEAR GS728TPP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs

Merk : NETGEAR

Artikelcode: GS728TPP-300EUS

Productnaam : GS728TPP



NETGEAR GS728TPP. Switch type: Managed, Switch-laag: L2/L3/L4. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24, Aantal geïnstalleerde SFP modules: 4. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 56 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Power over Ethernet (PoE). Rack-montage

Beheerfuncties		Design	
Switch type *	Managed	Overtollige fans ondersteuning	✓
Switch-laag	L2/L3/L4	Aantal ventilatoren	2 ventilator(en)
ARP-inspectie	✓	Certificering	CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	24	Type processor	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Processorfabrikant	ARM
Aantal geïnstalleerde SFP modules *	4	Processormodel	ARM Cortex-A55
Aantal USB Type-A-poorten	1	Frequentie van processor	800 MHz
Netwerk		Intern geheugen	512 MB
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x	Flash memory	64 MB
IPv4-routes	32	Geluidsniveau	33,3 dB
IPv6-routes	32	Mean time between failures (MTBF)	1252990 uur
VLAN=ondersteuning	✓	Energie	
Aantal VLANs	256	Stroombron *	AC
Data-uitwisseling		Stroomverbruik (typisch)	26 W
Switchingcapaciteit *	56 Gbit/s	Vermogensverbruik (max)	427 W
MAC-adrestabel *	16000 entries	Power over Ethernet (PoE)	
Latentie (10-100 Mbps)	8,871 µs	Power over Ethernet (PoE) *	✓
Latentie (1 Gbps)	4,701 µs	Aantal Power over Ethernet plus (PoE +)-poorten	24
Packet buffergeheugen	1,5 MB	Vermogen per poort Power over Ethernet (PoE)	380 W
Beveiliging		Eisen aan de omgeving	
DHCP-functies	DHCP snooping, DHCPv6 client	Bedrijfstemperatuur (T-T)	0 - 50 °C
Access Control List (ACL)	✓	Temperatuur bij opslag	-20 - 70 °C
Toegangsbeheerlijst (ACL) IPv4-vermeldingen	100	Relatieve vochtigheid in bedrijf (V-V)	0 - 90 procent
Multicast-functies		Luchtvochtigheid bij opslag	0 - 95 procent
Multicast-ondersteuning	✓	Gewicht en omvang	
Aantal gefilterde multicast-groepen	512	Breedte	440 mm
Design		Diepte	257 mm
Rack-montage *	✓	Hoogte	432 mm
Kleur van het product	Grijs	Gewicht	4,11 kg



0606449162356



606449162356

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date