tp-link

TP-Link Deco X20 (2-pack) Dual-band (2.4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) Wit Intern

Merk : TP-Link

Artikelcode: DECO X20(2-PACK)

Productnaam : Deco X20 (2-pack)

Qualcomm 1 GHz Quad-core, 2 LAN/WAN Gigabit Ethernet, 1201 Mbps (5 GHz) / 574 Mbps (2.4 GHz), D110 mm × 114 mm, 2-pack

TP-Link Deco X20 (2-pack). Kleur van het product: Wit, Soort antenne: Intern, Type product: Mesh-systeem. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 5 (802.11ac), WLAN gegevensoverdrachtsnelheid (max): 1775 Mbit/s. Firewall: SPI. AC-ingangsspanning: 100-240 V, Ingangsstroom AC-adapter: 0,4 A, AC-ingangsfrequentie: 50-60 Hz. Certificaten van naleving: CE, RoHS, Certificering: FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC

Design

Product type	Mesh system
Product colour *	White
LED indicators	Power
Antenna type *	Internal
Antennas quantity	4
Transmit power	FCC: <30 dBm, CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz)
Reset button	✔

Wireless LAN features

Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data transfer rate (max) *	1775 Mbit/s
WLAN data transfer rate (first band)	1201 Mbit/s
WLAN data transfer rate (second band)	574 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA-PSK, WPA2-PSK, WPA3
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Guest access	✔

Features

Built-in processor	✔
Processor cores	4

Ports & interfaces

DC-in jack	✔

Power

AC input voltage	100-240 V
AC adapter input current	0.4 A
AC input frequency	50-60 Hz
AC adapter output voltage	12 V
AC adapter output current	1 A

Certificates

Compliance certificates	CE, RoHS
Certification	FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC

Sustainability

Sustainability compliance	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	110 mm
Depth	110 mm
Height	114 mm

Packaging content

Number of products included	2 pc(s)
AC adapter included	✔
Number of units included	2 pc(s)

Features	
Quality of Service (QoS) support	✔
Firewall security	SPI
DHCP client	✔
DHCP server	✔
Parental control	✔

Ports & interfaces	
Ethernet LAN (RJ-45) ports *	2
Ethernet WAN	✔

Packaging content	
Ethernet cable	✔

Packaging data	
Package width	314 mm
Package depth	240 mm
Package height	125 mm
Package weight	1.66 kg

Logistics data	
Harmonized System (HS) code	85176990

6935364052287

6935364052423

0840030701115

840030701115