



# Lindy 38389 KVM-extender Ontvanger

**Merk :** Lindy **Artikelcode:** 38389

**Productnaam :** 38389

Lindy 38389. Soort: Ontvanger, Connectiviteitstechnologie: Bedraad, Maximaal bereik: 150 m. Poorttype zender video: HDMI, Poorttype zender lokaal toetsenbord/muis: USB. Poorttype ontvanger lokale video: HDMI, Poorttype ontvanger lokaal toetsenbord/muis: USB. USB-poorttype: USB Type-A. AC-adapter, uitgangsspanning: 24 V, AC-adapter, uitgangsstroom: 1 A



| Kenmerken                                   |                                                        | Energie                                     |                                                                |
|---------------------------------------------|--------------------------------------------------------|---------------------------------------------|----------------------------------------------------------------|
| Soort *                                     | Ontvanger                                              | AC-adapter, uitgangsspanning                | 24 V                                                           |
| Connectiviteitstechnologie *                | Bedraad                                                | AC-adapter, uitgangsstroom                  | 1 A                                                            |
| Maximaal bereik                             | 150 m                                                  | Verpakking                                  |                                                                |
| Ondersteundende kabel types                 | Cat6                                                   | Breedte verpakking                          | 220 mm                                                         |
| Resolutie (maximum digitaal)                | 3840 x 2160 Pixels                                     | Diepte verpakking                           | 70 mm                                                          |
| Maximale refresh snelheid                   | 60 Hz                                                  | Hoogte verpakking                           | 130 mm                                                         |
| Kleurdiepte                                 | 8 Bit                                                  | Gewicht verpakking                          | 579 g                                                          |
| Kleur van het product                       | Zwart                                                  | Inhoud van de verpakking                    |                                                                |
| Materiaal                                   | Metaal, Kunststof                                      | Gebruikershandleiding                       | ✓                                                              |
| LED-indicatoren                             | Link, Stroom, Video                                    | Eisen aan de omgeving                       |                                                                |
| Certificering                               | CE, UKCA, FCC, RoHS, REACH & California Proposition 65 | Bedrijfstemperatuur (T-T)                   | 0 - 40 °C                                                      |
| Zender                                      |                                                        | Temperatuur bij opslag                      | -20 - 60 °C                                                    |
| Poorttype zender video                      | HDMI                                                   | Relatieve vochtigheid in bedrijf (V-V)      | 20 - 90 procent                                                |
| Poorttype zender lokaal toetsenbord/muis    | USB                                                    | Luchtvochtigheid bij opslag                 | 20 - 90 procent                                                |
| Aantal RJ-45-poorten (zender)               | 1                                                      | Duurzaamheid                                |                                                                |
| Ontvanger                                   |                                                        | Naleving van duurzaamheid                   | ✓                                                              |
| Poorttype ontvanger lokale video            | HDMI                                                   | Overige specificaties                       |                                                                |
| Poorttype ontvanger lokaal toetsenbord/muis | USB                                                    | HDCP                                        | ✓                                                              |
| Aantal RJ-45-poorten (ontvanger)            | 1                                                      | HDCP versie                                 | 2.2                                                            |
| Poorten & interfaces                        |                                                        | Extended display identification data (EDID) | ✓                                                              |
| USB-poorttype                               | USB Type-A                                             | Certificaten van naleving                   | CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA |
| Aantal USB 2.0-poorten                      | 2                                                      | Technische details                          |                                                                |
| HDMI versie                                 | 2.0                                                    | Afmetingen (B x D x H)                      | 157 x 20 x 88 mm                                               |
| RS-232 port                                 | 1                                                      | Maximum resolutie                           | 3840 x 2160 Pixels                                             |
|                                             |                                                        | Gewicht                                     | 389 g                                                          |

**Logistieke gegevens**

|                       |           |
|-----------------------|-----------|
| Aantal per verpakking | 1 stuk(s) |
|-----------------------|-----------|



4002888383899

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-OCT-2024. Prints or copies of Information are only valid on the printed Publication date