

DeepCool DQ750-M-V2L power supply unit 750 W 20+4 pin ATX
Zwart

Merk : DeepCool

Artikelcode: DP-GD-DQ750-M-V2L

Productnaam : DQ750-M-V2L

DeepCool DQ750-M-V2L. Totaal vermogen: 750 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 550,700,850,1000 mm. Bedoeld voor: PC, 80 PLUS certificatie: 80 PLUS Gold, Mean time between failures (MTBF): 100000 uur. Kleur van het product: Zwart, Ventilator diameter: 12 cm, Aantal ventilatoren: 1 ventilator(en). Meegeleverde kabels: CPU, PCIe, Peripheral (Molex), SATA



Energie		Poorten & interfaces	
Totaal vermogen *	750 W	Lengte PCI Express-stroomkabel	50 cm
AC-ingangsspanning *	100 - 240 V	Lengte CPU-stroomkabel	70 cm
AC-ingangsfrequentie	47 - 63 Hz	ATX power connector (20+4 pin)	✓
Stroom	10 A	Bekabelingstype	Volledig modulair
Power Factor Correctie (PFC) type	Actief	Prestatie	
Gecombineerd vermogen (+3.3V)	110 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (+12V)	744 W	Bedoeld voor *	PC
Gecombineerd vermogen (+5V)	110 W	ATX version	2.31
Gecombineerd vermogen (-12V)	3,6 W	Mean time between failures (MTBF)	100000 uur
Gecombineerd vermogen(+5Vsb)	12,5 W	Certificering	CE, CB, CCC, EAC, FCC, KCC, RCM
Max huidige output (+3.3V)	20 A	Design	
Max huidige output(+12V)	62 A	Kleur van het product	Zwart
Max huidige output (+5V)	20 A	Ventilator diameter	12 cm
Max huidige output (-12V)	0,3 A	Aantal ventilatoren	1 ventilator(en)
Max huidige output (+5Vsb)	2,5 A	Ventilator locatie	Boven
Houd-tijd	16 ms	Aan/uitschakelaar	✓
Efficiëntie	90 procent	Eisen aan de omgeving	
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Kortsluiting, Onder spanning	Bedrijfstemperatuur (T-T)	0 - 40 °C
Poorten & interfaces		Inhoud van de verpakking	
Motherboard power connector *	20+4 pin ATX	Meegeleverde kabels	CPU, PCIe, Peripheral (Molex), SATA
Lengte stroomkabel moederbord	55 cm	Gewicht en omvang	
Aantal SATA power connectors	4	Breedte	150 mm
Lengte SATA-stroomkabel	550,700,850,1000 mm	Diepte	160 mm
Peripheral (Molex) power connectors (4-pin) *	2	Hoogte	86 mm
Lengte stroomkabel randapparaat (Molex)	450,600 mm	Verpakking	
EPS-voedingsconnector (4+4 pin)	✓	Type verpakking	Doos
PCI Express power connectors (6+2 pin)	2	Technische details	
		Certificaten van naleving	RoHS
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 84733020	



6933412798927

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date