

ASUS RT-AC1200 v.2 bedrade router Fast Ethernet Zwart

Merk : ASUS

Artikelcode: 90IG0550-BM3400

Productnaam : RT-AC1200 v.2

ASUS RT-AC1200 v.2. Netwerkstandaard: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, Ethernet interface type: Fast Ethernet, Bekabelingstechnologie: 10/100Base-T(X). Ondersteunde beveiligingsalgoritmen: 64-bit WEP, 128-bit WEP, SNMP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPS. Flash memory: 16 MB, Intern geheugen: 64 MB, Ondersteunt Windows: Windows 10, Windows 10 x64, Windows 8, Windows 8.1, Windows XP. Kleur van het product: Zwart, LED-indicatoren: LAN, Stroom, WAN, WLAN. AC-ingangsspanning: 110 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz, Stroom: 0.5 A



WAN-verbinding		Beveiliging	
Ethernet WAN *	✓	System event log	✓
DSL WAN *	✗	Technische details	
SIM-kaartsleuf *	✗	Digital Living Network Alliance (DLNA) gecertificeerd	✓
3G/4G USB modem compatibiliteit *	✗	Kenmerken	
Netwerk		Flash memory	16 MB
Netwerkstandaard *	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3	Intern geheugen	64 MB
Ethernet interface type *	Fast Ethernet	Ondersteunt Windows	Windows 10, Windows 10 x64, Windows 8, Windows 8.1, Windows XP
Bekabelingstechnologie	10/100Base-T(X)	Ondersteunt Mac-besturingssysteem	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Design	
Beheerfuncties		Kleur van het product *	Zwart
Web-gebaseerd management *	✓	LED-indicatoren	LAN, Stroom, WAN, WLAN
Quality of Service (QoS)	✓	Aan/uitschakelaar	✓
Universal Plug and Play (UPnP)	✓	Energie	
Reset button	✓	AC-ingangsspanning	110 - 240 V
WPS Push Button Security	✓	AC-ingangsfrequentie	50 - 60 Hz
Poorten & interfaces		Stroom	0.5 A
Aantal Ethernet LAN (RJ-45)-poorten *	5	Spanning	12 V
Protocollen		Gewicht en omvang	
DMZ support	✓	Breedte	117 mm
DHCP client *	✓	Diepte	126 mm
Beveiliging		Hoogte	34 mm
Ondersteunde beveiligingsalgoritmen *	64-bit WEP, 128-bit WEP, SNMP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPS	Gewicht	271 g

Beveiliging		Verpakking	
Firewall	✓	Meegeleverde kabels	LAN (RJ-45)
URL- filtering	✓	Snelstartgids	✓
Access Control List (ACL)	✓	Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85176990	



4718017254731

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date