



TP-Link ARCHER C24 draadloze router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) Wit

Merk : TP-Link

Artikelcode: ARCHER C24

Productnaam : ARCHER C24

TP-Link ARCHER C24. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 5 (802.11ac), WLAN gegevensoverdrachtsnelheid (max): 433 Mbit/s. Interfacetype Ethernet LAN: Fast Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100 Mbit/s, Netwerkstandaard: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Ondersteunde beveiligingsalgoritmen: WEP, WPA, WPA2. Type product: Router om neer te zetten, Kleur van het product: Wit. Meegeleverde kabels: LAN (RJ-45)



WAN-verbinding		Beveiliging	
Ethernet WAN *	✓	URL- filtering	✓
DSL WAN *	✗	Protocollen	
SIM-kaartsleuf *	✗	DHCP client	✓
3G/4G USB modem compatibiliteit *	✗	DHCP server	✓
Draadloos LAN		Design	
Wifi-band *	Dual-band (2.4 GHz / 5 GHz)	Kleur van het product	Wit
Wifi-standaard *	Wi-Fi 5 (802.11ac)	Type product *	Router om neer te zetten
WLAN gegevensoverdrachtsnelheid (max) *	433 Mbit/s	Inhoud van de verpakking	
Wi-Fi-standaarden	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Meegeleverde kabels	LAN (RJ-45)
Netwerk		Inclusief AC-adapter	✓
Ethernet LAN *	✓	Snelle installatiehandleiding	✓
Interfacetype Ethernet LAN *	Fast Ethernet	Duurzaamheid	
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Naleving van duurzaamheid	✓
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenne	
Mobiel netwerken		Antenne-ontwerp *	Extern
3G	✗	Antennas quantity	4
4G	✗	Kenmerken	
Poorten & interfaces		Type processor	✓
Aantal Ethernet LAN (RJ-45)-poorten *	5	Aantal processorkernen	1
USB-poort *	✗	Energie	
Geheugenkaart slot(s)	✗	Type stroombron *	AC
Aansluiting voor netstroomadapter	✓	Spanning	9 V
		Output current	0,6 A
		Eisen aan de omgeving	
		Bedrijfstemperatuur (T-T)	0 - 40 °C

Beheerfuncties		Eisen aan de omgeving	
Quality of Service (QoS)	✓	Temperatuur bij opslag	-40 - 60 °C
Reset button	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
WPS Push Button Security	✓	Luchtvochtigheid bij opslag	5 - 90 procent
Beveiliging		Gewicht en omvang	
Ondersteunde beveiligingsalgoritmen	WEP, WPA, WPA2	Breedte	115 mm
Firewall	✓	Diepte	106,7 mm
Ouderlijk toezicht	✓	Hoogte	24,3 mm
Technische details			
		Certificaten van naleving	RoHS



6935364089474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-SEP-2024. Prints or copies of Information are only valid on the printed Publication date