

Chieftec Value APB-400B8 power supply unit 400 W 20+4 pin ATX PS/2 Zilver

Merk : Chieftec**Productfamilie:** Value**Artikelcode:** APB-400B8**Productnaam :** APB-400B8

Chieftec Value APB-400B8. Totaal vermogen: 400 W, AC-ingangsspanning: 200 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 35 cm, Lengte SATA-stroomkabel: 150,350 mm. Bedoeld voor: Pc/server, Vormfactor van de voeding (PSU): PS/2, 80 PLUS certificatie: 80 PLUS. Kleur van het product: Zilver, Ventilator diameter: 12 cm, Aantal ventilatoren: 1 ventilator(en). Breedte: 140 mm, Diepte: 150 mm, Hoogte: 87 mm

Power		Ports & interfaces	
Total power *	400 W	EPS power connector (4+4 pin)	✓
AC input voltage *	200 - 240 V	PCI Express power connectors (6+2 pin)	1
AC input frequency	47 - 63 Hz	PCI Express power cable length	35 cm
Input current	3 A	CPU power connector (4+4 pin)	✓
Power factor	0.9	CPU power cable length	35 cm
Power Factor Correction (PFC) type	Active	Floppy drive power connector	1
Combined power (+3.3V)	100 W	Floppy disk drive connector	✓
Combined power (+12V)	360 W	Cabling type	Non-Modular
Combined power (+5V)	100 W	Performance	
Combined power (-12V)	3.6 W	80 PLUS certification *	80 PLUS
Combined power (+5Vsb)	12.5 W	Purpose *	PC/Server
Max output current (+3.3V)	17 A	Power supply unit (PSU) form factor *	PS/2
Max output current (+12V)	30 A	ATX version	2.3
Max output current (+5V)	16 A	Certification	80PLUS 230V EU
Max output current (-12V)	0.3 A	Design	
Max output current (+5Vsb)	2.5 A	Product colour	Silver
Power protection features	Over voltage, Overload, Short circuit, Under voltage	Fan diameter	12 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	20+4 pin ATX	Weight & dimensions	
Motherboard power cable length	35 cm	Width	140 mm
Number of SATA power connectors	3	Depth	150 mm
SATA power cable length	150,350 mm	Height	87 mm
Peripheral (Molex) power connectors (4-pin) *	2	Logistics data	
Peripheral (Molex) power cable length	150,350 mm	Harmonized System (HS) code	84733020



4710713230552

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-NOV-2024. Prints or copies of Information are only valid on the printed Publication date