



ASUS Prime B550M-A/CSM AMD B550 Socket AM4 micro ATX

Merk : ASUS

Artikelcode: 90MB14I0-M0EAYC

Productnaam : Prime B550M-A/CSM

ASUS Prime B550M-A/CSM. Processorfabrikant: AMD, Processor socket: Socket AM4, Compatibele processors: AMD Ryzen 3000 Series. Ondersteunde geheugen types: DDR4-SDRAM, Maximum intern geheugen: 128 GB, Geheugen slots type: DIMM. Ondersteunde opslagstationinterfaces: M.2, SATA III. Ethernet interface type: Gigabit Ethernet, LAN controller: Realtek RTL8111H. Component voor: PC, Moederbord form factor: micro ATX, Moederbord chipset familie: AMD



Processor		Rear panel I/O ports	
Processor manufacturer *	AMD	HDMI ports quantity *	1
Processor socket *	Socket AM4	DVI-D ports quantity *	1
Compatible processor series *	AMD Ryzen 3000 Series	Headphone outputs	1
Memory		Microphone in	✓
Supported memory types *	DDR4-SDRAM	Network	
Number of memory slots *	4	Ethernet LAN	✓
Memory slots type	DIMM	Ethernet interface type	Gigabit Ethernet
Supported memory clock speeds	2133,2400,2666,2800,3000,3200,3333,3466,3600,3733,3866,4000,4133,4266,4400,4600	LAN controller	Realtek RTL8111H
Maximum internal memory *	128 GB	Wi-Fi *	✗
Unbuffered memory	✓	Features	
Storage controllers		Motherboard chipset *	AMD B550
Supported storage drive interfaces *	M.2, SATA III	Audio chip	Realtek ALC887
Graphics		Audio output channels *	7.1 channels
On-board graphics card	✗	Product colour	Black, Silver
Internal I/O		Component for *	PC
USB 2.0 connectors *	2	Motherboard form factor *	micro ATX
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Motherboard chipset family *	AMD
Number of SATA III connectors *	4	Windows operating systems supported	Windows 10 x64
Front panel audio connector	✓	Expansion slots	
ATX Power connector (24-pin)	✓	PCI Express x1 (Gen 3.x) slots	2
CPU fan connector	✓	PCI Express x16 (Gen 4.x) slots	1
Number of chassis fan connectors	2		
EPS power connector (8-pin)	✓		

Rear panel I/O ports		BIOS	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	BIOS type *	UEFI AMI
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2	BIOS memory size	256 Mbit
Ethernet LAN (RJ-45) ports *	1	Clear CMOS jumper	✓
PS/2 ports quantity	1	Logistics data	
VGA (D-Sub) ports quantity *	1	Harmonized System (HS) code	84733020
		Weight & dimensions	
		Width	244 mm
		Depth	244 mm
		Height	51 mm
		Other features	
		Weight	845 g



4718017755535

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-DEC-2024. Prints or copies of Information are only valid on the printed Publication date