



TP-Link Archer AX23 draadloze router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Zwart

Merk : TP-Link

Productfamilie: Archer

Artikelcode: ARCHER AX23

Productnaam : Archer AX23

TP-Link Archer AX23. Type WAN-aansluiting: RJ-45. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 6 (802.11ax), WLAN gegevensoverdrachtsnelheid (max): 1800 Mbit/s. Interfacetype Ethernet LAN: Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s, Netwerkstandaard: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Ondersteunde beveiligingsalgoritmen: 64-bit WEP, 128-bit WEP, WMM, WPA, WPA-PSK, WPA2, WPA2-PSK, NAT functionality: Port Forwarding, Port Triggering, UPnP, DMZ. Type product: Router om neer te zetten, Kleur van het product: Zwart



WAN connection		Protocols	
Ethernet WAN *	✓	DHCP client	✓
SIM card slot *	✗	DHCP server	✓
WAN connection type	RJ-45	Universal Plug and Play (UPnP)	✓
Wireless LAN features		Design	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Product colour	Black
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Product type *	Tabletop router
WLAN data transfer rate (max) *	1800 Mbit/s	Certificates	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Certification	FCC, CE, RoHS
WLAN data transfer rate (first band)	574 Mbit/s	Packaging content	
WLAN data transfer rate (second band)	1201 Mbit/s	Cables included	LAN (RJ-45)
Network		AC adapter included	✓
Ethernet LAN *	✓	Warranty card	✓
Ethernet LAN interface type *	Gigabit Ethernet	Quick installation guide	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenna design *	External
Full duplex	✓	Antenna connector type	SMA
Flow control support	✓	Features	
Port forwarding	✓	Built-in processor	✓
Dynamic DNS (DDNS)	✓	Processor frequency	1500 MHz
Static route	✓	Processor cores	2
Ports & interfaces		Power	
Ethernet LAN (RJ-45) ports *	4	Power source type *	DC
		Output voltage	12 V
		Output current	1 A

Ports & interfaces		Operational conditions	
USB port *	✓	Operating temperature (T-T)	0 - 40 °C
USB 2.0 ports quantity	1	Operating relative humidity (H-H)	10 - 90%
DC-in jack	✓	System requirements	
Management features		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
Security		Windows operating systems supported	
Security algorithms	64-bit WEP, 128-bit WEP, WMM, WPA, WPA-PSK, WPA2, WPA2-PSK	Linux operating systems supported	✓
Guest access	✓	Mac operating systems supported	✓
Access Control List (ACL)	✓	Weight & dimensions	
IP address filtering	✓	Width	260.2 mm
URL filtering	✓	Depth	135 mm
System event log	✓	Height	41.6 mm
DMZ support	✓	Packaging data	
Network address translation (NAT)	✓	Package width	500 mm
NAT functionality	Port Forwarding, Port Triggering, UPnP, DMZ	Package depth	350 mm
		Package height	395 mm
		Package weight	730 g
		Logistics data	
		Harmonized System (HS) code	85176990



4897098687048



4897098683927

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.