

ASUS Prime 850W Gold (AP-850G) power supply unit 20+4 pin ATX ATX Zwart, Wit

Merk : ASUS

Artikelcode: 90YE00U0-B0NB00

Productnaam : Prime 850W Gold (AP-850G)

ASUS Prime 850W Gold (AP-850G). Totaal vermogen: 850 W, AC-ingangsspanning: 100 - 240 V, Gecombineerd vermogen (+3.3V): 110 W. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 61 cm, Lengte SATA-stroomkabel: 120,400 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Wit, Type koeling: Actief, Aantal ventilatoren: 1 ventilator(en). Meegeleverde kabels: AC, CPU, PCIe, Peripheral (Molex), SATA



Energie		Poorten & interfaces	
Totaal vermogen *	850 W	Lengte PCI Express-stroomkabel	67,5 cm
AC-ingangsspanning *	100 - 240 V	CPU power connector (4+4 pin)	✓
Gecombineerd vermogen (+3.3V)	110 W	Lengte CPU-stroomkabel	65 cm
Gecombineerd vermogen (+12V)	846 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+5V)	110 W	Prestatie	
Gecombineerd vermogen (-12V)	3,6 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen(+5Vsb)	12,5 W	Bedoeld voor *	PC
Max huidige output (+3.3V)	20 A	Vormfactor van de voeding (PSU) *	ATX
Max huidige output(+12V)	70,5 A	ATX version	3.0
Max huidige output (+5V)	20 A	Bearing technologie	DBB
Max huidige output (-12V)	0,3 A	Design	
Max huidige output (+5Vsb)	2,5 A	Kleur van het product	Zwart, Wit
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning	Type koeling	Actief
Poorten & interfaces		Aantal ventilatoren	1 ventilator(en)
Motherboard power connector *	20+4 pin ATX	Ventilator locatie	Boven
Lengte stroomkabel moederbord	61 cm	Aan/uitschakelaar	✓
Aantal SATA power connectors	5	Inhoud van de verpakking	
Lengte SATA-stroomkabel	120,400 mm	Meegeleverde kabels	AC, CPU, PCIe, Peripheral (Molex), SATA
Peripheral (Molex) power connectors (4-pin) *	3	Certificaten	
Lengte stroomkabel randapparaat (Molex)	150,400 mm	Certificaten van naleving	RoHS
PCI Express power connectors (8-pin)	3	Gewicht en omvang	
PCI Express-voedingsconnectoren (16-pins)	1	Breedte	150 mm
		Diepte	150 mm
		Hoogte	86 mm
		Gewicht	1,5 kg

Verpakking

Gewicht verpakking	2,72 kg
Type verpakking	Doos



4711387192849



0197105192843



197105192843

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.