



## Equip 128422 USB 3.2 Gen 2x2 C naar C U-plug kabel, 2,0 m, zwart, M/M, PD240W, 4K/60Hz, 20Gbps

**Merk :** Equip

**Artikelcode:** 128422

**Productnaam :** 128422 USB 3.2 Gen 2x2 C naar C U-plug kabel, 2,0 m, zwart, M/M, PD240W, 4K/60Hz, 20Gbps

USB 3.2 Gen 2x2 C naar C U-plug kabel, 2,0 m, zwart, M/M, PD240W, 4K/60Hz, 20Gbps

Equip 128422 USB 3.2 Gen 2x2 C naar C U-plug kabel, 2,0 m, zwart, M/M, PD240W, 4K/60Hz, 20Gbps:

De Equip 128422 USB 3.2 Gen 2x2 C to C U Plug Cable is een hoogwaardige, 2,0 meter lange kabel die is ontworpen voor superieure gegevensoverdracht en stroomvoorziening. Met zijn gestroomlijnde zwarte ontwerp ondersteunt deze male-to-male kabel gegevensoverdrachtsnelheden tot 20 Gbps, wat zorgt voor snelle en efficiënte bestandsoverdracht. Hij ondersteunt ook 4K/60Hz video-uitvoer, waardoor hij ideaal is voor beeldschermen met een hoge resolutie. Daarnaast is de kabel voorzien van Power Delivery (PD) 240W, waardoor compatibele apparaten snel en krachtig kunnen worden opgeladen. Deze veelzijdige kabel is perfect voor gebruikers die op zoek zijn naar robuuste connectiviteitsoplossingen voor zowel professioneel als persoonlijk gebruik.



| Features                              |                          | Features                           |            |
|---------------------------------------|--------------------------|------------------------------------|------------|
| USB version *                         | USB4 Gen 2x2             | High Dynamic Range (HDR) supported | ✓          |
| Connector 1 *                         | USB C                    | HDCP                               | ✓          |
| Connector 2 *                         | USB C                    | HDCP version                       | 2.2        |
| Connector 1 gender *                  | Male                     | <b>Weight &amp; dimensions</b>     |            |
| Connector 2 gender *                  | Male                     | Cable length *                     | 2 m        |
| Connector 1 form factor               | Straight                 | Weight                             | 79 g       |
| Connector 2 form factor               | Angled                   | <b>Packaging data</b>              |            |
| Connector contacts plating            | Nickel                   | Package type                       | Polybag    |
| Cable jacket material                 | Polyvinyl chloride (PVC) | Package width                      | 175 mm     |
| Cable jacket type                     | Braided                  | Package depth                      | 275 mm     |
| Conductor material                    | Copper                   | Package height                     | 40 mm      |
| Connector shield material             | Aluminium                | Package weight                     | 85 g       |
| Maximum data transfer rate            | 20 Gbit/s                | <b>Packaging content</b>           |            |
| Product colour *                      | Silver                   | Quantity per pack *                | 1 pc(s)    |
| Cable type                            | Round cable              | <b>Certificates</b>                |            |
| Plug and Play                         | ✓                        | Compliance certificates            | CE, RoHS   |
| Fast charging                         | ✓                        | <b>Logistics data</b>              |            |
| USB Power Delivery (USB PD)           | ✓                        | Products per master (outer) case   | 100 pc(s)  |
| USB Power Delivery revision           | 3.1                      | Master (outer) case width          | 450 mm     |
| USB Power Delivery up to              | 240 W                    | Master (outer) case length         | 300 mm     |
| USB Type-C DisplayPort Alternate Mode | ✓                        | Master (outer) case height         | 230 mm     |
| Maximum resolution                    | 3840 x 2160 pixels       | Master (outer) case gross weight   | 9.1 kg     |
| Maximum refresh rate                  | 240 Hz                   | Harmonized System (HS) code        | 8544421900 |
|                                       |                          | Country of origin                  | China      |



4015867237694

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-FEB-2025. Prints or copies of Information are only valid on the printed Publication date