


TP-Link Archer BE3600 draadloze router 2.5 Gigabit Ethernet Dualband (2.4 GHz / 5 GHz) Zwart

Merk: TP-Link Productfamilie: Archer Artikelcode: ARCHER BE230

Productnaam: BE3600







WAN connection		Management features	
Ethernet WAN *	✓	Quality of Service (QoS) support	✓
SIM card slot *	×	Reset button	✓
3G/4G USB modem compatibility *	×	WPS push button	✓
WAN connection type	RJ-45	MU-MIMO technology	✓
Wireless LAN features		Number of data streams	4x4
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) *	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 7 (802.11be) 2882 Mbit/s	Security	
		Security algorithms	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3
Wi-Fi standards	Wi-Fi 7 (802.11be)	Firewall	✓
WLAN data transfer rate (first band)	2882 Mbit/s	Guest access	✓
WLAN data transfer rate (second band)	688 Mbit/s	Access Control List (ACL)	✓
Modulation	4096-QAM, OFDMA	Parental control	✓
Network	• •	DDoS protection	✓
Ethernet LAN *	✓	IP address filtering	✓
Ethernet LAN interface type *	2.5 Gigabit Ethernet	DMZ support	✓
Ethernet LAN data rates	1000,2500 Mbit/s	Protocols	
Cabling technology	10/100/1000Base-T(X)	DHCP server	✓
Port forwarding	✓	Universal Plug and Play (UPnP)	✓
Port triggering	✓	Design	
Dynamic DNS (DDNS)	✓	Product colour	Black
Number of guest networks (2.4 GHz)	1	On/off switch	✓
Number of guest networks (5 GHz)	1	Product type *	Tabletop router
Support Samba (storage)	1	Certificates	
Built-in FTP server	✓	Compliance certificates	CE, Federal Communications
Media server	1	compliance certificates	Commission (FCC), RoHS
VPN support	OpenVPN Server PPTP VPN Server L2TP VPN Server WireGuard VPN Server	Antenna	
		Antenna design * Antennas quantity	External 4

Ports & interfaces		Features	
USB port *	✓	Works with Amazon Alexa	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Works with the Google Assistant	✓
		Firmware upgradeable	✓
Management features		Power	
Web-based management		Power source type *	AC
		Output voltage	12 V
		Output current	1.5 A
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	10 - 90%









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.