## GIGABYTE P550SS ICE power supply unit 550 W 20+4 pin ATX ATX Wit

Merk: GIGABYTE Artikelcode: GP-P550SS ICE EU

**Productnaam:** P550SS ICE

GIGABYTE P550SS ICE. Totaal vermogen: 550 W, AC-ingangsspanning: 155-240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 60 cm, Bekabelingstype: Niet-modulair. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Silver. Kleur van het product: Wit, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 140 mm, Diepte: 150 mm, Hoogte: 86 mm





Power		Ports & interfaces	
Total power *	550 W	ATX power connector (20+4 pin)	✓
AC input voltage *	155-240 V	Floppy drive power connector	2
AC input frequency	50/60 Hz	Floppy disk drive connector	/
Input current	6.3 A	PCI Express connector	1
Power Factor Correction (PFC) type	Active	Cabling type	Non-Modular
Combined power (+3.3V)	100 W	5 71	Non-Modulai
Combined power (+12V)	549.6 W	Performance	
Combined power (+5V)	100 W	80 PLUS certification *	80 PLUS Silver
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor	ATX
Max output current (+3.3V)	20 A	*	
Max output current (+12V)	45.8 A	ATX version	3.1
Max output current (+5V)	20 A	Bearing technology	Ball bearing
Max output current (-12V)	0.3 A	Mean time between failures (MTBF)	100000 h
Max output current (+5Vsb)	3 A	Design	
Hold time	16 ms	Product colour	White
Efficiency	90%	Cooling type	Active
Power Good signal delay range	100 - 150 ms	Fan diameter	12 cm
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Number of fans Fan location	1 fan(s) Top
	Olider Voltage	On/off switch	1
Ports & interfaces		Martin In Call and a state of	
Motherboard power connector *	20+4 pin ATX	Weight & dimensions	
Motherboard power cable length	60 cm	Width	140 mm
Number of SATA power connectors	5	Depth	150 mm
Peripheral (Molex) power connectors (4-pin) *	4	Height Weight	86 mm 1.95 kg
PCI Express power connectors (6+2 pin)	2	Packaging data	
		Package width	254 mm

Ports & interfaces		Packaging data	
CPU power connector (4+4 pin)	•	Package depth	206 mm
		Package height	117 mm
		Package weight	2.11 kg
		Package type	Box
		Logistics data	
		Warranty period	3 year(s)



4719331554910

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.