



**MSI MAG A850GL PCIE5 II power supply unit 850 W 20+4 pin ATX  
ATX Zwart**

**Merk :** MSI

**Productfamilie:** MAG

**Artikelcode:** MAG A850GL  
PCIE5 II

**Productnaam :** A850GL PCIE5  
II

MSI MAG A850GL PCIE5 II. Totaal vermogen: 850 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 60 cm, Lengte SATA-stroomkabel: 150,500 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 150 mm, Diepte: 140 mm, Hoogte: 86 mm



| Energie                                       |                                                                                          | Poorten & interfaces                      |                   |
|-----------------------------------------------|------------------------------------------------------------------------------------------|-------------------------------------------|-------------------|
| Totaal vermogen *                             | 850 W                                                                                    | EPS power connector (8-pin)               | ✗                 |
| AC-ingangsspanning *                          | 100 - 240 V                                                                              | EPS-voedingsconnector (4+4 pin)           | ✓                 |
| AC-ingangsfrequentie                          | 47 - 63 Hz                                                                               | PCI Express power connectors (6+2 pin)    | 4                 |
| Power Factor Correctie (PFC) type             | Actief                                                                                   | PCI Express-voedingsconnectoren (16-pins) | 1                 |
| Aantal +12V rail(s)                           | 1                                                                                        | CPU power connector (4+4 pin)             | ✓                 |
| Gecombineerd vermogen (+3.3V)                 | 110 W                                                                                    | Bekabelingstype                           | Volledig modulair |
| Gecombineerd vermogen (+12V)                  | 846 W                                                                                    | <b>Prestatie</b>                          |                   |
| Gecombineerd vermogen (+5V)                   | 110 W                                                                                    | 80 PLUS certificatie *                    | 80 PLUS Gold      |
| Gecombineerd vermogen (-12V)                  | 3,6 W                                                                                    | Bedoeld voor *                            | PC                |
| Gecombineerd vermogen(+5Vsb)                  | 12,5 W                                                                                   | Vormfactor van de voeding (PSU) *         | ATX               |
| Max huidige output (+3.3V)                    | 20 A                                                                                     | ATX version                               | 3.1               |
| Max huidige output(+12V)                      | 70,5 A                                                                                   | Bearing technologie                       | FDB               |
| Max huidige output (+5V)                      | 20 A                                                                                     | <b>Design</b>                             |                   |
| Max huidige output (-12V)                     | 0,3 A                                                                                    | Kleur van het product                     | Zwart             |
| Max huidige output (+5Vsb)                    | 2,5 A                                                                                    | Type koeling                              | Actief            |
| Efficiëntie                                   | 90 procent                                                                               | Ventilator diameter                       | 12 cm             |
| Stroomspanning bescherming                    | Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning | Aantal ventilatoren                       | 1 ventilator(en)  |
| <b>Poorten &amp; interfaces</b>               |                                                                                          | Aan/uitschakelaar                         | ✓                 |
| Motherboard power connector *                 | 20+4 pin ATX                                                                             | <b>Gewicht en omvang</b>                  |                   |
| Lengte stroomkabel moederbord                 | 60 cm                                                                                    | Breedte                                   | 150 mm            |
| Aantal SATA power connectors                  | 8                                                                                        | Diepte                                    | 140 mm            |
| Lengte SATA-stroomkabel                       | 150,500 mm                                                                               | Hoogte                                    | 86 mm             |
| Peripheral (Molex) power connectors (4-pin) * | 4                                                                                        | <b>Verpakking</b>                         |                   |
| Lengte stroomkabel randapparaat (Molex)       | 500 mm                                                                                   | Type verpakking                           | Doos              |



4711377246682



0824142377079



824142377079

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.