

2m USB-C Laadkabel met Zijschroefvergrendeling, 240W (5A) PD EPR, Siliconen Mantel met Gevlochten Nylon, USB 2.0 Laptop Oplaadkabel, USB-IF Gecertificeerd, Robuuste USB-C Laadkabel

Productcode: S2CEPR2M-USBSL-CABLE



Connect a charger to a USB Power Delivery (PD) 3.1-enabled device, using this USB-C Charging Cable. The USB-C charger cord delivers up to 240W of Extended Power Range (EPR) Power Delivery and 5A output for fast charging. The connector markings enable quick visual identification, distinguishing this cable from other similar-looking or unmarked USB-C cables. Eliminate guesswork and always choose the appropriate Type-C cable to support full 240W charging.

Quality Construction

Designed for frequent use, the USB-C EPR Charging Cable features a rugged TPE outer jacket for increased wear resistance. The durable nickel-plated connectors are rated to operate beyond 10,000 insertion cycles, enhancing its durability and longevity.

Charge Mobile Devices On The Go

Charge a USB-C device with a USB-C wall charger, car charger, or power bank. The 3-foot (0.9-meter) USB Type-C cable is the ideal length for desk and mobile workstations, commuters, in-car use or to reduce clutter when syncing with a USB-C laptop.

Power a Laptop

With up to 5A of output, the USB-C Charger Cord supports up to 240W of Power Delivery to charge a USB-C laptop, or fast charge a tablet or smartphone. To use, connect the cable from a USB-C laptop to a USB-C wall charger.

Certificaties, rapporten en compatibiliteit



Toepassingen

Eigenschappen

- **USB-C EPR CHARGING CABLE:** Type-C cable supports Power Delivery 3.1 Extended Power Range (EPR); Up to 240W to high-power USB-C laptops; 10ft length provides extra reach; Connector markings identify data/power specs; Choose the right 240W cable at-a-glance
- **USB-IF CERTIFIED:** The USB C Cable is USB-IF certified with integrated E-marker chip, for consistent Power Delivery output to USB-C hosts and peripherals; When using certified cables, reliable performance and compatibility is guaranteed
- **QUALITY CONSTRUCTION:** Nickel-plated connectors rated beyond 10,000 insertions; Thicker 24/28AWG wire for consistent power; Withstands 120° bends; Braided Aluminum shield protects from EMI; Durable TPE outer jacket is halogen-free and RoHS compliant
- **TOEPASSINGEN:** Compatibel met apparatuur met USB-C Power Delivery; Schroefvergrendeling voor schijfbehuizingen & externe opslag; Ideaal voor high-performance laptops zoals 16" MacBook Pro/Max M-series; Ondersteunt USB 2.0 voor algemene file transfer/sync
- **PERFORMANCE:** 240W/5A PD 3.1 EPR, 48V; Backward Compatible w/140W/100W/60W; USB 2.0 Type-C (480Mbps); 10-foot (3-meter) cable; Color: Black; O.D.: 0.16in (4.0mm); TPE Jacket w/Braided Aluminum Shield; NOTE: USB-C video (DP Alt Mode) is not supported

Hardware

Garantiebeleid	Lifetime
Connectormateriaal	Nikkel
Type kabelmantel	Silicone with Braided Nylon

Prestaties

MTBF	Rated beyond 10,000 insertions
------	--------------------------------

Connector(en)

Connector A	1 - USB Type-C (24-pin) USB 2.0 (480Mbps)
Connector B	1 - USB Type-C (24-pin) USB 2.0 (480Mbps)

Voeding

	Power Delivery	240W
Gebruiksomgeving		
	Bedrijfstemperatuur	0°C - 50°C (32°F - 122°F)
	Opslagtemperatuur	-20°C - 70°C (-4°F - 158°F)
	Vochtigheid	5% - 85%
Fysieke eigenschappen		
	Kleur	Zwart
	Stijl connector	Recht
	Draaddikte	30 AWG
	Type behuizing	ABS
	Kabellengte	6.6 ft [2 m]
	Buitendiameter kabel	0.2 in [4.7 mm]
	Lengte product	6.6 ft [2.0 m]
	Breedte product	0.8 in [2.0 cm]
	Hoogte product	0.3 in [6.8 mm]
	Gewicht product	3.0 oz [84.0 g]
Verpakkingsinformatie		
	Package Length	5.0 in [12.8 cm]
	Package Width	8.7 in [22.0 cm]
	Package Height	0.7 in [1.8 cm]
	Verzendgewicht (verpakt)	3.2 oz [90.0 g]
Wat wordt er meegeleverd		
	Meegeleverd	1 - 2m USB-C Charging Cable M/M - Side Locking

* Uitvoering en specificaties van het product zijn zonder aankondiging vatbaar voor wijzigingen.