

be quiet! Silent Loop 3 360 mm Processor Alles-in-één vloeistofkoeler 12 cm Zwart 1 stuk(s)



Merk : be quiet!

Artikelcode: BW025

Productnaam : Silent Loop 3 360 mm

be quiet! Silent Loop 3 360 mm. Soort: Alles-in-één vloeistofkoeler, Ventilator diameter: 12 cm, Luchtstroom: 130,3 m³/uur, Maximum luchtdruk: 3,96 mmH₂O, Type lager: Vloeistof dynamisch lager (FDB). Breedte: 120 mm, Diepte: 52 mm, Hoogte: 397 mm. Kleur van het product: Zwart



Performance		Weight & dimensions	
Suitable location *	Processor	Radiator width	12 cm
Type *	All-in-one liquid cooler	Radiator depth	39.7 cm
Fan diameter	12 cm	Radiator height	2.7 cm
Supported processor sockets	Intel LGA1851, LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1200 (Socket H5), LGA 1700, Socket AM4, Socket AM5, Socket TR4, Socket TR5	Depth	52 mm
		Tube length	40 cm
Noise level (low speed)	19.8 dB	Waterblock width	8 cm
Noise level (high speed)	38.8 dB	Waterblock depth	5.6 cm
Maximum airflow	76.7 cfm	Waterblock height	9.35 cm
Airflow	130.3 m ³ /h	Height	397 mm
Maximum air pressure	3.96 mmH ₂ O	Weight	1.77 kg
Pulse-width modulation (PWM) support	✓	Fan dimensions (W x D x H)	120 x 120 x 25 mm
Bearing type	Fluid Dynamic Bearing (FDB)	Cable length	0.5 m
Pump connector	4-pin	Package width	206 mm
Quantity per pack	1 pc(s)	Package depth	461 mm
Pump motor speed	3500 RPM	Package height	138 mm
Pump motor speed (min)	1700 RPM	Package weight	3 kg
Pump motor speed (max)	3500 RPM	Technical details	
Fan speed (max)	2500 RPM	Sustainability certificates	Triman
Fan's mean time to failure (MTTF)	300000 h	Warranty period	3 year(s)
Design		Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, UKCA, WEEE
Product colour *	Black	Packaging content	
Radiator material	Aluminum	Package type	Box
Base plate material	Copper	Mounting kit	✓
Number of fans	3 fan(s)	Screws included	✓
Illumination LED	✓	Manual	✓
Illumination colour	Multi	CPU bracket(s)	✓
LED connector type	3-pin	Other features	
Fan connector	4-pin	Thermal grease	✓
Power		Logistics data	
Fan power consumption	3.6 W	Products per shipping (inner) case	4 pc(s)
LED voltage	5 V	Shipping (inner) case width	43 cm
Fan voltage	12 V	Shipping (inner) case length	47.6 cm

Power		Logistics data	
Fan current	0.3 A	Shipping (inner) case height	33.6 cm
Weight & dimensions		Shipping (inner) case gross weight	13.2 kg
Width	120 mm		



4260052192542

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-FEB-2025. Prints or copies of Information are only valid on the printed Publication date