



MSI MAG A750GN PCIE5 power supply unit 750 W 20+4 pin ATX ATX Zwart

Merk : MSI

Artikelcode: MAG A750GN PCIE5

Productnaam : MAG A750GN PCIE5

MSI MAG A750GN PCIE5. Totaal vermogen: 750 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 150,450 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 150 mm, Diepte: 140 mm, Hoogte: 86 mm



Energie		Poorten & interfaces	
Totaal vermogen *	750 W	Lengte stroomkabel randapparaat (Molex)	500 mm
AC-ingangsspanning *	100 - 240 V	EPS power connector (8-pin)	✗
AC-ingangsfrequentie	47 - 63 Hz	EPS-voedingsconnector (4+4 pin)	✓
Maximale ingangsstroom (@110V)	47 A	PCI Express power connectors (6+2 pin)	2
Maximale ingangsstroom (@220V)	63 A	CPU power connector (4+4 pin)	✓
Power Factor Correctie (PFC) type	Actief	ATX Power connector (24-pin)	✗
Aantal +12V rail(s)	1	ATX power connector (20+4 pin)	✗
Gecombineerd vermogen (+3.3V)	110 W	Bekabelingstype	Niet-modulair
Gecombineerd vermogen (+12V)	750 W	Prestatie	
Gecombineerd vermogen (+5V)	110 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (-12V)	3,6 W	Bedoeld voor *	PC
Gecombineerd vermogen(+5Vsb)	15 W	Vormfactor van de voeding (PSU) *	ATX
Max huidige output (+3.3V)	20 A	ATX version	3.1
Max huidige output(+12V)	62,5 A	Bearing technologie	Hoes
Max huidige output (+5V)	20 A	Design	
Max huidige output (-12V)	0,3 A	Kleur van het product	Zwart
Max huidige output (+5Vsb)	3 A	Type koeling	Actief
Efficiëntie	90 procent	Ventilator diameter	12 cm
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting	Aantal ventilatoren	1 ventilator(en)
Poorten & interfaces		Belichting	✗
Motherboard power connector *	20+4 pin ATX	Aan/uitschakelaar	✓
Lengte stroomkabel moederbord	55 cm	Gewicht en omvang	
Aantal SATA power connectors	4	Breedte	150 mm
Lengte SATA-stroomkabel	150,450 mm	Diepte	140 mm
Peripheral (Molex) power connectors (4-pin) *	4	Hoogte	86 mm
		Verpakking	
		Type verpakking	Doos



4711377244282

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.