




## COUGAR CGR-POLAR-X2-1050 power supply unit 1050 W 20+4 pin ATX ATX Zilver

**Merk :** COUGAR

**Artikelcode:** 31PX105001P01

**Productnaam :** CGR-POLAR-X2-1050

COUGAR CGR-POLAR-X2-1050. Totaal vermogen: 1050 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 65 cm, Lengte SATA-stroomkabel: 120,500 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Platinum. Kleur van het product: Zilver, Type koeling: Actief, Ventilator diameter: 13,5 cm. Certificaten van naleving: EAC, TÜV mark, Federal Communications Commission (FCC), RoHS, CCC, CE



| Energie                                       |                                                                                          | Poorten & interfaces                   |                                                                       |
|-----------------------------------------------|------------------------------------------------------------------------------------------|----------------------------------------|-----------------------------------------------------------------------|
| Totaal vermogen *                             | 1050 W                                                                                   | ATX power connector (20+4 pin)         | ✓                                                                     |
| AC-ingangsspanning *                          | 100 - 240 V                                                                              | PCI Express connector                  | ✓                                                                     |
| AC-ingangsfrequentie                          | 47 - 63 Hz                                                                               | Bekabelingstype                        | Volledig modulair                                                     |
| Stroom                                        | 15 - 7 A                                                                                 | <b>Prestatie</b>                       |                                                                       |
| Gecombineerd vermogen (+3.3V)                 | 100 W                                                                                    | 80 PLUS certificatie *                 | 80 PLUS Platinum                                                      |
| Gecombineerd vermogen (+12V)                  | 1050 W                                                                                   | Bedoeld voor *                         | PC                                                                    |
| Gecombineerd vermogen (+5V)                   | 100 W                                                                                    | Vormfactor van de voeding (PSU) *      | ATX                                                                   |
| Gecombineerd vermogen (-12V)                  | 3,6 W                                                                                    | ATX version                            | 3.1                                                                   |
| Gecombineerd vermogen(+5Vsb)                  | 15 W                                                                                     | Stille modus                           | ✓                                                                     |
| Max huidige output (+3.3V)                    | 20 A                                                                                     | Geluidsniveau                          | 22 dB                                                                 |
| Max huidige output(+12V)                      | 87,5 A                                                                                   | Bearing technologie                    | HDB                                                                   |
| Max huidige output (+5V)                      | 20 A                                                                                     | Mean time between failures (MTBF)      | 100000 uur                                                            |
| Max huidige output (-12V)                     | 0,3 A                                                                                    | <b>Design</b>                          |                                                                       |
| Max huidige output (+5Vsb)                    | 3 A                                                                                      | Kleur van het product                  | Zilver                                                                |
| Efficiëntie                                   | 90 procent                                                                               | Type koeling                           | Actief                                                                |
| Stroomspanning bescherming                    | Oververhitting, Overstroom, Te hoog vermogen, Onder spanning, Overspanning, Kortsluiting | Ventilator diameter                    | 13,5 cm                                                               |
| <b>Poorten &amp; interfaces</b>               |                                                                                          | Aantal ventilatoren                    | 1 ventilator(en)                                                      |
| Motherboard power connector *                 | 20+4 pin ATX                                                                             | Aan/uitschakelaar                      | ✓                                                                     |
| Lengte stroomkabel moederbord                 | 65 cm                                                                                    | <b>Eisen aan de omgeving</b>           |                                                                       |
| Aantal SATA power connectors                  | 12                                                                                       | Bedrijfstemperatuur (T-T)              | 10 - 50 °C                                                            |
| Aantal PATA power aansluiters                 | 4                                                                                        | Temperatuur bij opslag                 | -40 - 70 °C                                                           |
| Lengte SATA-stroomkabel                       | 120,500 mm                                                                               | Relatieve vochtigheid in bedrijf (V-V) | 20 - 85 procent                                                       |
| Peripheral (Molex) power connectors (4-pin) * | 4                                                                                        | Luchtvochtigheid bij opslag            | 5 - 95 procent                                                        |
| Lengte stroomkabel randapparaat (Molex)       | 120,500 mm                                                                               | <b>Certificaten</b>                    |                                                                       |
| EPS power connector (8-pin)                   | ✓                                                                                        | Certificaten van naleving              | EAC, TÜV mark, Federal Communications Commission (FCC), RoHS, CCC, CE |
| PCI Express power connectors (6+2 pin)        | 6                                                                                        | <b>Gewicht en omvang</b>               |                                                                       |
| PCI Express power connectors (8-pin)          | 1                                                                                        | Breedte                                | 150 mm                                                                |
| PCI Express-voedingsconnectoren (12+4-pins)   | 1                                                                                        | Diepte                                 | 180 mm                                                                |
|                                               |                                                                                          | Hoogte                                 | 86 mm                                                                 |

| Poorten & interfaces                                      |        | Gewicht en omvang   |         |
|-----------------------------------------------------------|--------|---------------------|---------|
| Lengte van de PCI Express-voedingsconnectoren (12+4 pins) | 650 mm | Gewicht             | 2,09 kg |
| CPU power connector (4+4 pin)                             | ✓      | Verpakking          |         |
| Lengte CPU-stroomkabel                                    | 65 cm  | Breedte verpakking  | 229 mm  |
|                                                           |        | Diepte verpakking   | 331 mm  |
|                                                           |        | Hoogte verpakking   | 107 mm  |
|                                                           |        | Gewicht verpakking  | 3,59 kg |
|                                                           |        | Type verpakking     | Doos    |
|                                                           |        | Logistieke gegevens |         |
|                                                           |        | Land van herkomst   | China   |



4710483775413

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.