

HDMI Receiver Over IP Network for the IH2006 Product Series, 4K 60Hz, Driverless, AVoIP, Includes Mounting Kit, Receiver Only

Productcode: IH2006-HDMI-RX



The AVoIP HDMI Receiver extends a 4K 60Hz HDMI signal over an existing TCP/IP network when paired with a compatible transmitter, keeping systems secure from unauthorized access and physical damage.

The plug-and-play design requires no drivers or software and is compatible with all major operating systems, including Windows, macOS, and Linux, as well as hardware platforms like Intel, AMD, Snapdragon/ARM, and Apple Silicon.

Easily expand your setup by adding multiple receivers to create a one-to-many configuration, making it easy to scale with your business needs for flexible and future-proof IP Video or KVM distribution.

Receiver features a durable metal housing with mounting kits for wall or under-desk installation, plus rubber feet for desktop stability. RS232 and 3.5mm audio passthrough ports enable serial and audio extension.

Certificaties, rapporten en compatibiliteit



Toepassingen

- Reduce the need for physical access to a computer or server, improving security and efficiency
- Enables secure, high-performance connections between workstations and studio equipment
- Allows operators to manage critical systems from a safe or more convenient location

Eigenschappen

- **AVoIP HDMI RECEIVER:** When paired with an IH2006 transmitter (sold separately), extend a 4K 60Hz HDMI signal over a TCP/IP network to a remote display, enabling high-quality video distribution while keeping the source system secure
- **SCALABLE SETUP:** Easily expand your setup by adding multiple receivers to create a one-to-many configuration, making it easy to scale with your business needs for flexible and future-proof IP Video or KVM distribution
- **NO DRIVERS OR SOFTWARE:** Requires no configuration to get it working; Compatible with any operating system including Windows, macOS and Linux, as well as all hardware platforms such as Intel, AMD, Snapdragon/ARM and Apple Silicon
- **AUDIO & SERIAL EXTENSION:** Equipped with a three-wire RS232 port for serial extension and a 3.5mm audio passthrough port, ensuring seamless transmission of audio and control signals over the network
- **SECURE & FLEXIBLE INSTALLATION:** Durable metal housing with included mounting kit for wall or under-desk installation; Rubber feet prevent slipping for desktop use; Ideal for industrial and professional environments

Hardware

Garantiebeleid	2 Years
Audio	Ja
KVM-poorten	1
PC-videotype	HDMI
Rack-monteerbaar	Nee
Inclusief kabels	Nee

Prestaties

Schermmenu & sneltoetsen	Nee
--------------------------	-----

Video Revision	HDMI 2.0
IP-controle	Ja
Hot-Key Selection	Nee
Maximale digitale resoluties	3840 x 2160 @ 60Hz
Audiospecificaties	HDMI - 2 Channel Audio
Poortselectie-ondersteuning	Niet van toepassing

Connector(en)

Console-aansluiting(en)	1 - Aansluitblok (3 draden)
	1 - 3.5mm Stereo Female 3 pos
	1 - RJ-45
	1 - HDMI
Andere aansluiting(en)	1 - USB Micro-B (5-polig)

Software

Besturingssystemen	Vereist geen Drivers of Software
--------------------	----------------------------------

Indicatoren

LED-indicatoren	1 - Power LED: Solid Blue: Indicates the unit is receiving Power 1 - Sync LED: Off: Transmitter and Receiver have no established a connection Slow Orange Flash: Transmitter and Receiver are connected via Gigabit Ethernet but no Video is transmitting Quick Orange Flash: Transmitter and Receiver are connected via 100Mbps Ethernet but no Video is transmitting Solid Orange: Video is transmitting
-----------------	---

Voeding

Voedingsbron	Inclusief wisselstroomadapter
Ingangsspanning	100 - 240 AC
Ingangsstroom	0.3A
Uitgangsspanning	5 DC
Uitgangsstroom	2A
Polariteit pin midden	Positief
Stekkertype	M
Vermogensopname	10W

Gebruiksomgeving

Bedrijfstemperatuur	-20°C to 60°C (-4°F to 140°F)
Opslagtemperatuur	-30°C to 70°C (-22°F to 158°F)
Vochtigheid	0% ~ 90% RH (niet condenserend)

Fysieke eigenschappen

Kleur	Zwart
Type behuizing	Staal
Lengte product	0.0 in [0.0 mm]
Breedte product	0.0 in [0.0 mm]
Hoogte product	0.0 in [0.0 mm]
Gewicht product	0.0 oz [0.0 g]

Verpakkingsinformatie

Lengte Verpakking	5.9 in [14.9 cm]
Package Width	7.8 in [19.9 cm]
Package Height	3.1 in [8.0 cm]
Verzendgewicht	1.1 lb [0.5 kg]

(verpakt)

Wat wordt er
meegeleverd

Meegeleverd

1 - IP HDMI Receiver

1 - Set rubberen voetjes

1 - RS-232 Terminal Header

1 - Montage materiaal

1 - Universele voedingsadapter (NA/GB/EU/ANZ)

* Uitvoering en specificaties van het product zijn zonder aankondiging vatbaar voor wijzigingen.