

GIGABYTE UD750GM PG5 V2 power supply unit 750 W 20+4 pin ATX ATX Zwart

Merk : GIGABYTE

Artikelcode: GP-UD750GM PG5 V2 EU

Productnaam : UD750GM PG5 V2

GIGABYTE UD750GM PG5 V2. Totaal vermogen: 750 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 61 cm, Lengte SATA-stroomkabel: 150,600 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 150 mm, Diepte: 140 mm, Hoogte: 86 mm



Energie		Poorten & interfaces	
Totaal vermogen *	750 W	Lengte PCI Express-stroomkabel	60 cm
AC-ingangsspanning *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC-ingangsfrequentie	50/60 Hz	Lengte CPU-stroomkabel	65 cm
Stroom	12 - 6.5 A	Floppy drive power connector	1
Power factor	0,9	PCI Express connector	✓
Power Factor Correctie (PFC) type	Actief	Aantal EPS-aansluitingen	2
Gecombineerd vermogen (+3.3V)	105 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+12V)	750 W	Prestatie	
Gecombineerd vermogen (+5V)	105 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (-12V)	3,6 W	Bedoeld voor *	PC
Gecombineerd vermogen(+5Vsb)	15 W	Vormfactor van de voeding (PSU) *	ATX
Max huidige output (+3.3V)	20 A	ATX version	3.1
Max huidige output(+12V)	62,5 A	Bearing technologie	HYB
Max huidige output (+5V)	20 A	Mean time between failures (MTBF)	100000 uur
Max huidige output (-12V)	0,3 A	Design	
Max huidige output (+5Vsb)	3 A	Kleur van het product	Zwart
Houd-tijd	16 ms	Type koeling	Actief
Efficiëntie	90 procent	Ventilator diameter	12 cm
Stroomspanning bescherming	Overstroom, Te hoog vermogen,	Aantal ventilatoren	1 ventilator(en)
	Overspanning, Oververhitting, Kortsluiting, Onder spanning	Aan/uitschakelaar	✓
Poorten & interfaces		Gewicht en omvang	
Motherboard power connector *	20+4 pin ATX	Breedte	150 mm
Lengte stroomkabel moederbord	61 cm	Diepte	140 mm
Aantal SATA power connectors	8	Hoogte	86 mm
Lengte SATA-stroomkabel	150,600 mm	Gewicht	2,34 kg
Peripheral (Molex) power connectors (4-pin) *	3	Verpakking	
Lengte stroomkabel randapparaat (Molex)	150,500 mm	Breedte verpakking	618 mm
PCI Express power connectors (6+2 pin)	4	Diepte verpakking	269 mm
		Hoogte verpakking	211 mm
		Gewicht verpakking	2,5 kg

Poorten & interfaces		Verpakking	
PCI Express-voedingsconnectoren (12+4-pins)	1	Type verpakking	Doos
Lengte van de PCI Express-voedingsconnectoren (12+4 pins)	700 mm	Logistieke gegevens	
		Garantieperiode	5 jaar



4719331555870

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.