


COVER




IB-1827MCP-C31

M.2 NVMe and SATA SSD Enclosure
dust and shock proof



1x




1x



1x



1x





1x



1x



Legacy USB standards	Current USB standards	Data transfer rate
USB 3.0 = USB 3.1 (Gen 1)	= USB 3.2 Gen 1	= 5 Gbit/s
USB 3.1 = USB 3.1 (Gen 2)	= USB 3.2 Gen 2	= 10 Gbit/s
USB 3.2 (Gen 2x2)	= USB 3.2 Gen 2x2	= 20 Gbit/s
	= USB4® Gen 2x1	= 10 Gbit/s
	= USB4® Gen 2x2	= 20 Gbit/s
	= USB4® Gen 3x2	= 40 Gbit/s



www.icybox.de

BACK



© Copyright 2025 by RaidSonic Technology GmbH. All Rights Reserved.
The information contained in this manual is believed to be accurate and reliable.
RaidSonic Technology GmbH assumes no responsibility for any errors contained in
this manual. RaidSonic Technology GmbH reserves the right to make changes in the
specifications and/or design of the above-mentioned product without prior notice.
The diagrams contained in this manual may also not fully represent the product that
you are using and are there for illustration purposes only. USB Type-C and USB-C
are registered trademarks of USB Implementers Forum. RaidSonic Technology GmbH
assumes no responsibility for any differences between the product mentioned in this
manual and the product you may have.

