

iivama ProLite T2754MSC-B2AG computer monitor 68,6 cm (27") 1920 x 1080 Pixels Full HD LED Touchscreen Multi-gebruiker Zwart

Merk : iivama

Productfamilie: ProLite

Artikelcode: T2754MSC-B2AG

Productnaam : T2754MSC-B2AG

iivama ProLite T2754MSC-B2AG. Beeldscherm diagonaal: 68,6 cm (27"), Resolutie: 1920 x 1080 Pixels, HD type: Full HD, Display technologie: LED, Responstijd: 4 ms, Oorspronkelijke beeldverhouding: 16:9, Kijkhoek, horizontaal: 178°, Kijkhoek, verticaal: 178°. Ingebouwde luidsprekers. Ingebouwde USB-hub, Versie USB-hub: 3.2 Gen 1 (3.1 Gen 1). VESA-montage, In hoogte verstelbaar. Kleur van het product: Zwart



Beeldscherm		Ergonomie	
Beeldscherm diagonaal *	68,6 cm (27")	On Screen Display (OSD)	✓
Resolutie *	1920 x 1080 Pixels	On Screen Display (OSD)-talen	Duits, Engels, Spaans, Frans, Italiaans, Japans, Nederlands, Pools, Portugees, Russisch
HD type *	Full HD	Energie	
Oorspronkelijke beeldverhouding *	16:9	Energie-efficiëntieklasse (SDR) *	E
Display technologie *	LED	Energie-efficiëntieklasse (HDR) *	Niet beschikbaar
Soort paneel *	IPS	Energieverbruik (SDR) per 1000 uur *	21 kWu
Touchscreen *	✓	Stroomverbruik (typisch) *	27 W
Touch screen type	Multi-gebruiker	Stroomverbruik (in standby) *	0,5 W
Touchscreen technologie	Projected capacitive-systeem	Stroomverbruik (indien uit)	0,3 W
Hoeveelheid simultane aanraakpunten	10	AC-adapter, uitgangsspanning	19 V
Helderheid (typisch)	300 cd/m ²	Soort voeding	Extern
Helderheid	300 cd/m ²	Gewicht en omvang	
Responstijd *	4 ms	Breedte apparaat (met standaard)	612 mm
Type reactietijdmeting	GTG (Gray to Gray)	Diepte apparaat (met standaard)	241 mm
Beeldscherm vorm *	Flat	Hoogte apparaat (met standaard)	387 mm
Typische contrastverhouding *	1000:1	Gewicht (met standaard)	6,6 kg
Maximale refresh snelheid *	83 Hz	Verpakking	
Kijkhoek, horizontaal	178°	Breedte verpakking	688 mm
Kijkhoek, verticaal	178°	Diepte verpakking	148 mm
Beeldscherm, aantal kleuren *	16,7 miljoen kleuren	Hoogte verpakking	477 mm
Pixel pitch	0,311 x 0,311 mm	Gewicht verpakking	9,2 kg
Frequentiebereik horizontaal	30 - 83 kHz	USB kabel lengte	1,8 m
Grootte beeld (horizontaal)	59,8 cm	Inhoud van de verpakking	
Grootte beeld (verticaal)	33,6 cm	Meegeleverde kabels	AC, USB, HDMI
Schermdiagonaal in centimeters	68,6 cm	Snelstartgids	✓
Kleurdiepte	8 Bit	HDMI-kabellengte	1,8 m
Prestatie		Lengte stroomkabel	1,8 m
Knippervrije technologie	✓	Duurzaamheid	
Laag-blauw-licht-technologie	✓	Duurzaamheidscertificaten	ErP
Multimedia			
Aantal luidsprekers	2		
Gemiddeld vermogen	4 W		
Ingebouwde luidsprekers *	✓		

Multimedia		Overige specificaties	
Ingebouwde camera *	✗	Compatibele besturingssystemen	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Design			
Kleur van het product *	Zwart		
Rand voorzijde	Zwart	Positienauwkeurigheid	2 mm
Poorten & interfaces			
Ingebouwde USB-hub *	✓		
Versie USB-hub	3.2 Gen 1 (3.1 Gen 1)	Gebruikersknoppen	luminance (contrast, brightness, i-Style Color, adv. contrast, eco, auto off), Image settings (pixel clock, phase, horizontal position, vertical position, aspect ratio), Color settings (gamma, 6- axis, color temp), OSD (OSD horizontal position, OSD vertical position, OSD time, language), Extra (reset, DDC/CI, signal select, OverDrive, opening logo, information)
Aantal downstreampoorten	2		
USB Touch port	✓		
VGA (D-Sub)poort(en)	1		
HDMI *	✓		
Aantal HDMI-poorten	1	Verpakkingsinhoud	Screwdriver
HDCP	✓		
Ergonomie			
VESA-montage *	✓	Actief weergavegebied (b x h)	597,89 x 336,31 mm
Paneelmontage-interface	100 x 100 mm	Touch-methode	finger, glove (latex), capacitive stylus
Verbeterd kabelbeheer	✓	Aantal USB-aansluitingen	2
In hoogte verstelbaar *	✓	Gewicht	6,6 kg
Verstelbare hoogte (max)	13,8 cm	Hoogte	387 mm
kantel aanpassingen	✓	Breedte	612 mm
		Diepte	241 mm
		Bedieningspaneel	Power, menu, + / volume, - eco, auto / exit / signal select
		Certificaten van naleving	CE, EAC, REACH, RoHS, UKCA, WEEE
		Mean time between failures (MTBF)	50000 uur



4948570125807

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-FEB-2026. Prints or copies of Information are only valid on the printed Publication date