

KNIPEX Quality – Made in Germany



High Leverage Combination Plier

Even more Power!

for all areas of application





Even more Power for easier working!

02 High Leverage Combination Plier



Powerful gripping and pulling thanks to high transmission ratio



Induction hardened cutting edges also for piano wire

- ▶ **effort saving working:**
more than 35 % saving in power
- ▶ **for heaviest duty:**
high-quality materials, oil-hardened and tempered
- ▶ **cuts piano wire:**
cutting edges additionally induction hardened
- ▶ **optimised gripping surfaces for comfortable working:**
finish 2, 5 and 6 with ergonomically shaped, two-colour dual component handles
- ▶ **all-round use:**
gripping zones for round and flat material

KNIPEX **spezial**

KNIPEX High Leverage Combination Pliers with optimum position of the joint facilitate cutting as well as powerful gripping, bending and pulling.

Requires 35% less effort

Cutting a hard wire of 2.0 mm dia. with a High Leverage Combination Plier of 180 mm length requires a handforce of only 318 N (31.8 kp) instead of 486 N (48.6 kp) with a common Combination Plier of same length.



	Art. No.	Length mm	Head	Handles	Cutting Capacities Ø mm		g
					hard wire	piano wire	
	02 01 180	180	polished	plastic	2.5	2.0	205
	02 01 200	200			2.8	2.2	280
	02 01 225	225			3.0	2.5	360
	02 02 180	180	polished	two-colour dual component	2.5	2.0	235
	02 02 200	200			2.8	2.2	330
	02 02 225	225			3.0	2.5	400
	02 05 180	180	chrome plated	two-colour dual component	2.5	2.0	235
	02 05 200	200			2.8	2.2	330
	02 05 225	225			3.0	2.5	400
	02 06 180	180	chrome plated	insulated with two-colour dual component handles, VDE tested	2.5	2.0	240
	02 06 200	200			2.8	2.2	335
	02 06 225	225			3.0	2.5	405
	02 07 200	200	chrome plated	plastic dipped, VDE tested	2.5	2.0	385
	02 07 225	225			2.8	2.2	490

Distributed by:

KNIPEX-Werk
C. Gustav Putsch KG

P.O. Box 12 04 05
D-42334 Wuppertal
Oberkamper Straße 13
D-42349 Wuppertal

Phone: +49 2 02/47 94-0
Fax: +49 2 02/47 74 94

Internet: www.knipex.de
E-Mail: info@knipex.de