

Delock Converter 3G-SDI > HDMI

Description

This Delock converter can be used to convert an HD- or 3G-SDI signal to an HDMI signal. You can connect e. g. a camera with HD-SDI output to an HDMI monitor. The SDI signal is transmitted via a conventional 75 Ohm coaxial cable with BNC connectors.



Specification

- Connector:
 - Input: 1 x BNC female (SDI)
 - Output: 1 x BNC female (SDI, pass-through)
 - 1 x HDMI-A female
 - 1 x DC Power 5 V
- Supported resolution:
 - SD 480i, 525i und 625i
 - HD 720p 24, 25, 30, 50 und 60 Hz
 - HD 1080i 50, 60 Hz
 - HD 1080p 24, 25, 30, 50 und 60 Hz
- Supported data rate: 270 Mb/s ~ 2.97 Gb/s
- Supports 8 channels of 48 kHz audio (PCM)
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 100 x 70 x 25 mm

Item No. 93237



EAN	4043619932375
-----	---------------

Country of origin	China
-------------------	-------

Package content

- HD-SDI > HDMI Converter
- Mounting brackets and screws
- Power supply 5 V

Package

- Box

Images

