

Delock Cable mini DisplayPort 1.2 male with screw > DVI male 4K Active black 3 m

Description

This cable enables you to connect a DVI monitor through a free mini DisplayPort interface. The cable supports a resolution up to Ultra HD (4K) and is backward compatible to Full-HD 1080p. The screw of the mini DisplayPort connector secures the connection and prevents accidental unplugging of the cable.



ca. 3 m

Specification

- Connector: mini DisplayPort 20 pin male with screw > DVI-D (Dual Link) 24+1 male
- Input = mini DisplayPort; Output = DVI
- Screw type: #4-40, thread type UNC, thread class 3A, American Standard Screw
- Chipset: Parade PS171
- DisplayPort 1.2 specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Gold-plated connector
- Active cable, for graphics cards with DP and DP++ output
- Supports a resolution up to 4K (4096 x 2160 pixel @ 24 Hz or 3840 x 2160 pixel @ 30 Hz) - depending on the system and the connected hardware
- Supports HDCP 1.3
- Supports Eyefinity
- 2 x ferrite core
- Cable length: ca. 3 m (incl. connector)
- Colour: black
- OS independent, no driver installation necessary

System requirements

- A free mini DisplayPort female port

Package content


- Cable mini DisplayPort to DVI

Item no. 83727

EAN: 4043619837274

Country of origin: China

Package: Poly bag



Images



ca. 3 m

General

Specification: DisplayPort 1.2
HDCP 1.3

Interface

Connector 1: 1 x mini DisplayPort 20 pin male
Connector 2: 1 x DVI 24+1 male with screws

Technical characteristics

Chipset: Parade PS171
Maximum screen resolution: 3840 x 2160 @ 30 Hz
4096 x 2160 @ 24 Hz

Physical characteristics

Ferrite core: 2 x
Cable diameter: 5.5 mm
Pin finishing: gold-plated
Conductor gauge: 32 AWG
Screw type: #4-40 UNC
Length: 3 m
Colour: black