

be quiet! System Power B9 power supply unit 350 W 20+4 pin ATX ATX Grijs

Merk : be quiet!

Artikelcode: BN207

Productnaam : System Power B9

be quiet! System Power B9. Totaal vermogen: 350 W, AC-ingangsspanning: 200 - 240 V, AC-ingangsfrequentie: 50 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 45 cm, Lengte SATA-stroomkabel: 400 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS. Kleur van het product: Grijs, Ventilator diameter: 12 cm, Aantal ventilatoren: 1 ventilator(en). Meegeleverde kabels: AC



Energie		Poorten & interfaces	
Totaal vermogen *	350 W	CPU power connector (4+4 pin)	✓
AC-ingangsspanning *	200 - 240 V	Lengte CPU-stroomkabel	45 cm
AC-ingangsfrequentie	50 Hz	Bekabelingstype	Niet-modulair
Stroom	3 A	Prestatie	
Power factor	0,95	80 PLUS certificatie *	80 PLUS
Power Factor Correctie (PFC) type	Actief	Bedoeld voor *	PC
Gecombineerd vermogen (+3.3V)	103 W	Vormfactor van de voeding (PSU) *	ATX
Gecombineerd vermogen (+12V)	324 W	ATX version	2.4
Gecombineerd vermogen (+5V)	103 W	Stille modus	✓
Gecombineerd vermogen (-12V)	3,6 W	Certificering	CE, CB, TÜV, RCM, CU
Gecombineerd vermogen(+5Vsb)	12,5 W	Design	
Max huidige output (+3.3V)	19 A	Kleur van het product	Grijs
Max output current (+12V1)	20 A	Ventilator diameter	12 cm
Max output current (+12V2)	16 A	Aantal ventilatoren	1 ventilator(en)
Max huidige output (+5V)	15 A	Belichting	✗
Max huidige output (-12V)	0,3 A	Aan/uitschakelaar	✓
Max huidige output (+5Vsb)	2,5 A	Inhoud van de verpakking	
Houd-tijd	17 ms	Meegeleverde kabels	AC
Efficiëntie	87 procent	Gewicht en omvang	
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning	Breedte	150 mm
Poorten & interfaces		Diepte	140 mm
Motherboard power connector *	20+4 pin ATX	Hoogte	86 mm
Lengte stroomkabel moederbord	45 cm	Gewicht	1,6 kg
Aantal SATA power connectors	4	Technische details	
Aantal PATA power aansluiters	2	Duurzaamheidscertificaten	RoHS, ENERGY STAR
Lengte SATA-stroomkabel	400 mm	Logistieke gegevens	
PCI Express power connectors (6+2 pin)	1	Code geharmoniseerd systeem (HS)	84733020
Lengte PCI Express-stroomkabel	45 cm	Overige specificaties	
		Geluidsniveau (stille modus, <30%)	12,1 dB
		Geluidsniveau (stille modus, 50%)	12,3 dB
		Geluidsniveau (volle belastingmode, 100%)	24,9 dB



4260052185995

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date