## be quiet! System Power 10 power supply unit 450 W 20+4 pin ATX ATX Zwart

Merk: be quiet! Artikelcode: BN326

**Productnaam:** System Power 10

be quiet! System Power 10. Totaal vermogen: 450 W, AC-ingangsspanning: 200 - 240 V, AC-ingangsfrequentie: 50 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 450,550,570,670,690,790 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Bronze. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 140 mm, Diepte: 86 mm, Hoogte: 150





Power		Performance	
Total power *	450 W	Power supply unit (PSU) form factor	
AC input voltage *	200 - 240 V	*	ATX
AC input frequency	50 Hz	ATX version	2.52
Input current	4 A	EPS version	2.92
Power factor	0.95	Noise level	19.2 dB
Power Factor Correction (PFC) type	Active	Bearing technology	Sleeve
Combined power (+3.3V)	100 W	Mean time between failures (MTBF)	100000 h
Combined power (+12V)	450 W	Certification	CB, TÜV, cRUus, cTUVus, RCM
Combined power (+5V)	100 W	Certification	(Australia), BSMI, CU (Russia)
Combined power (-12V)	3.6 W	Country of origin	Germany
Combined power (+5Vsb)	15 W	Design	
Max output current (+3.3V)	20 A	Product colour	Black
Max output current (+12V)	37.5 A	Cooling type	Active
Max output current (+5V)	20 A	Fan diameter	12 cm
Max output current (-12V)	0.3 A	Number of fans	1 fan(s)
Max output current (+5Vsb)	3 A	Fan speed	0 - 1800 RPM
Hold time	17 ms	On/off switch	1
Efficiency	88.5%		
Power Good signal delay range	100 - 150 ms	Operational conditions	
•		Operating temperature (T-T)	0 - 40 °C
•	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit,	Operating temperature (T-T) Storage temperature (T-T)	-20 - 70 °C
Power Good signal delay range	100 - 150 ms Over current, Over power, Over	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 70 °C 0 - 90%
Power Good signal delay range	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit,	Operating temperature (T-T) Storage temperature (T-T)	-20 - 70 °C
Power Good signal delay range  Power protection features	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit,	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 70 °C 0 - 90%
Power Good signal delay range  Power protection features  Ports & interfaces	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-20 - 70 °C 0 - 90%
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage 20+4 pin ATX 55 cm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	-20 - 70 °C 0 - 90% 0 - 95%
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage 20+4 pin ATX 55 cm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width	-20 - 70 °C 0 - 90% 0 - 95%
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length  Number of SATA power connectors	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage  20+4 pin ATX 55 cm 5	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	-20 - 70 °C 0 - 90% 0 - 95% 140 mm 86 mm
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length  Number of SATA power connectors  Number of PATA power connectors	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage  20+4 pin ATX 55 cm 5	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	-20 - 70 °C 0 - 90% 0 - 95% 140 mm 86 mm 150 mm
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length  Number of SATA power connectors  Number of PATA power connectors  SATA power cable length  Peripheral (Molex) power	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage  20+4 pin ATX 55 cm 5 1 450,550,570,670,690,790 mm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging data Manual	-20 - 70 °C 0 - 90% 0 - 95% 140 mm 86 mm 150 mm 1.74 kg
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length  Number of SATA power connectors  Number of PATA power connectors  SATA power cable length  Peripheral (Molex) power  connectors (4-pin) *  Peripheral (Molex) power cable  length  PCI Express power connectors (6+2	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage  20+4 pin ATX 55 cm 5 1 450,550,570,670,690,790 mm 1 790 mm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)  Weight & dimensions  Width Depth Height Weight  Packaging data  Manual Manual languages	-20 - 70 °C 0 - 90% 0 - 95%  140 mm 86 mm 150 mm 1.74 kg  German, English, Spanish, French, Polish, Russian
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length  Number of SATA power connectors  Number of PATA power connectors  SATA power cable length  Peripheral (Molex) power  connectors (4-pin) *  Peripheral (Molex) power cable  length  PCI Express power connectors (6+2  pin)	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage  20+4 pin ATX 55 cm 5 1 450,550,570,670,690,790 mm 1 790 mm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)  Weight & dimensions  Width Depth Height Weight  Packaging data  Manual Manual languages  Package width	-20 - 70 °C 0 - 90% 0 - 95%  140 mm 86 mm 150 mm 1.74 kg  German, English, Spanish, French, Polish, Russian 195 mm
Power Good signal delay range  Power protection features  Ports & interfaces  Motherboard power connector *  Motherboard power cable length  Number of SATA power connectors  Number of PATA power connectors  SATA power cable length  Peripheral (Molex) power  connectors (4-pin) *  Peripheral (Molex) power cable  length  PCI Express power connectors (6+2	100 - 150 ms Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage  20+4 pin ATX 55 cm 5 1 450,550,570,670,690,790 mm 1 790 mm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)  Weight & dimensions  Width Depth Height Weight  Packaging data  Manual Manual languages	-20 - 70 °C 0 - 90% 0 - 95%  140 mm 86 mm 150 mm 1.74 kg  German, English, Spanish, French, Polish, Russian

Ports & interfaces		Packaging data	
CPU power cable length ATX power connector (20+4 pin)	60 cm ✓	Package weight	2.1 kg
		Technical details	
Cabling type	Non-Modular	Sustainability certificates	ENERGY STAR, ErP
Performance		Warranty period	5 year(s)
80 PLUS certification * Purpose *	80 PLUS Bronze PC	Compliance certificates	CCC, CE, Federal Communications Commission (FCC), RoHS, WEEE
		Other features	
		Screws included	<b>✓</b>
		Noise level (silent mode, <30%)	8.7 dB
		Noise level (quiet mode, 50%)	9.8 dB
		Noise level (full-load mode, 100%)	19.2 dB



4260052189061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.