be quiet! System Power 10 power supply unit 650 W 20+4 pin ATX ATX Zwart

Merk : be quiet!

Artikelcode: BN328

Productnaam : System Power 10

be quiet! System Power 10. Totaal vermogen: 650 W, AC-ingangsspanning: 200 - 240 V, ACingangsfrequentie: 50 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 450,550,570,670,690,790 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Bronze. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 140 mm, Diepte: 86 mm, Hoogte: 150 mm





Power

Power		Performance	
Total power *	650 W	Power supply unit (PSU) form factor	АТХ
AC input voltage *	200 - 240 V	*	
AC input frequency	50 Hz	ATX version	2.52
Input current	5 A	EPS version	2.92
Power factor	0.95	Noise level	30.7 dB
Power Factor Correction (PFC) type	Active	Bearing technology	Sleeve
Combined power (+3.3V)	120 W	Mean time between failures (MTBF)	
Combined power (+12V)	650 W	Certification	CB, TÜV, cRUus, cTUVus, RCM (Australia), BSMI, CU (Russia)
Combined power (+5V)	120 W	Country of origin	Germany
Combined power (-12V)	3.6 W	Design	
Combined power (+5Vsb)	15 W	Product colour	Black
Max output current (+3.3V)	20 A 54.17 A		Black Active
Max output current (+12V) Max output current (+5V)	20 A	Cooling type Fan diameter	12 cm
Max output current (+5V) Max output current (-12V)	0.3 A	Number of fans	1 fan(s)
Max output current (+5Vsb)	3 A	Fan speed	0 - 2100 RPM
Hold time	17 ms	On/off switch	
Efficiency	88.5%		1
Power Good signal delay range	100 - 150 ms	Operational conditions	
Tower cood signal delay range	Over current, Over power, Over	Operating temperature (T-T)	0 - 40 °C
Power protection features	voltage, Overheating, Short circuit,	Storage temperature (T-T)	-20 - 70 °C
	Under voltage	Operating relative humidity (H-H)	0 - 90%
Ports & interfaces		Storage relative humidity (H-H)	0 - 95%
Motherboard power connector *	20+4 pin ATX	Weight & dimensions	
Motherboard power cable length	55 cm	Width	140 mm
Number of SATA power connectors	5	Depth	86 mm
Number of PATA power connectors	1	Height	150 mm
SATA power cable length	450,550,570,670,690,790 mm	Weight	1.86 kg
Peripheral (Molex) power connectors (4-pin) *	1	Packaging data	
Peripheral (Molex) power cable length	790 mm	Manual	✓ German, English, Spanish, French,
PCI Express power connectors (6+2 pin)	2	Manual languages	Polish, Russian
PCI Express power cable length	50 cm	Package width	195 mm
CPU P4 connector (4-pin)	1	Package depth	268 mm
	-	Package height	97 mm

Deufeumennes

Ports & interfaces		Packaging data	
CPU power connector (4+4 pin)	1	Package weight	2.3 kg
CPU power cable length ATX power connector (20+4 pin) Cabling type	60 cm ✔ Non-Modular	Technical details	
		Sustainability certificates	ENERGY STAR, ErP
		Warranty period	5 year(s)
Performance		Compliance certificates	CCC, CE, Federal Communications Commission (FCC), RoHS, WEEE
80 PLUS certification * Purpose *	80 PLUS Bronze PC	Other features	
		Screws included	1
		Noise level (silent mode, <30%)	8.9 dB
		Noise level (quiet mode, 50%)	11.2 dB

Noise level (full-load mode, 100%) 30.7 dB



4260052189085

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.