

Delock Adapter USB Type-C™ male > VGA female (DP Alt Mode)

Description

This Delock adapter is suitable for the connection of a VGA monitor to a computer with USB-C™ interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.



Specification

- Connectors:
 - 1 x USB Type-C™ male >
 - 1 x VGA 15 pin female
- Chipset: Realtek RTD2169U
- VGA port with nuts
- DisplayPort 1.4 specification
- Resolution up to WUXGA 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of analogue video signals
- USB bus powered
- Plug & Play
- Gold-plated connectors
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: black

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.4, Mac ex OS 10.13
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to VGA adapter

Item no. 62994

EAN: 4043619629947

Country of origin: China

Package: Retail Box



Images



General

| | |
|-----------------------------|--|
| Function: | Plug & Play |
| Specification: | DisplayPort 1.4 |
| Supported operating system: | Chrome OS Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile ex Linux Kernel 4.4.x ex Mac OS 10.13 |

Interface

| | |
|---------|-----------------------|
| Output: | 1 x VGA 15 pin female |
| Input: | 1 x USB Type-C™ male |

Technical characteristics

| | |
|----------------------------|---------------------|
| Chipset: | Realtek RTD2169U |
| Maximum screen resolution: | 1920 x 1200 @ 60 Hz |
| Signal transmission: | video |

Physical characteristics

| | |
|----------------------|-------------|
| Ferrite core: | 1 x |
| Cable length: | 20 cm |
| Connector finishing: | gold-plated |
| Colour: | black |