



ICY BOX IB-DK2242AC Bedraad USB 3.2 Gen 1 (3.1 Gen 1) Type-A Zwart

Merk : ICY BOX

Artikelcode: 60333

Productnaam : IB-DK2242AC

ICY BOX IB-DK2242AC. Connectiviteitstechnologie: Bedraad, Hostinterface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, Type aansluitplug: 3,5 mm. Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s. Kleur van het product: Zwart, Overdrachtssnelheid: 5000 Gbit/s, HD type: 5K Ultra HD. Type stroombron: AC, AC-ingangsspanning: 100-240 V, AC-ingangsfrequentie: 50 - 60 Hz. Breedte: 70 mm, Diepte: 195 mm, Hoogte: 125 mm



Poorten & interfaces		Energie	
Connectiviteitstechnologie *	Bedraad	Output current	2,25 A
Hostinterface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Software	
Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type A *	6	Ondersteunt Windows	✓
Aantal DisplayPorts	2	Mac-compatibiliteit	✓
Microfoon, line-in ingang *	✓	Ondersteunt Mac-besturingssysteem	✓
Hoofdtelefoonuitgangen *	1	Gewicht en omvang	
Type aansluitplug	3,5 mm	Breedte	70 mm
Aansluiting voor netstroomadapter	✓	Diepte	195 mm
Netwerk		Hoogte	125 mm
Ethernet LAN *	✓	Gewicht	404 g
Aantal Ethernet LAN (RJ-45)-poorten	1	Verpakking	
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Aantal per verpakking	1 stuk(s)
Wake-on-LAN	✓	Breedte verpakking	90 mm
Prestatie		Diepte verpakking	290 mm
Geïntegreerde geheugenkaartlezer *	✗	Hoogte verpakking	155 mm
Overdrachtssnelheid	5000 Gbit/s	Gewicht verpakking	1,29 kg
HD type	5K Ultra HD	Inhoud van de verpakking	
Resolutie (maximum digitaal)	5120 x 2880 Pixels	Meegeleverde kabels	USB Type-C to USB Type-B, USB, USB Type-A naar USB Type-B
Aantal displays ondersteund	2	Inclusief AC-adapter	✓
Maximale refresh snelheid	60 Hz	Gebbruikershandleiding	✓
Kleur van het product *	Zwart	Meegeleverde drivers	✓
Aan/uitschakelaar	✓	Logistieke gegevens	
UASP-ondersteuning	✓	Hoeveelheid per (buitenste) hoofdverpakking	9 stuk(s)
Materiaal behuizing	Acrylonitriëlbutoadieenstyreen (ABS), Polycarbonaat (PC)	(Buitenste) hoofdverpakking breedte	310 mm
Land van herkomst	China	(Buitenste) hoofdverpakking lengte	500 mm
Energie		(Buitenste) hoofdverpakking hoogte	310 mm
Type stroombron	AC		
AC-ingangsspanning	100-240 V		

Energie

AC-ingangsfrequentie	50 - 60 Hz
Stroom	1.3 A
Spanning	20 V

Logistieke gegevens

(Buitenste) hoofdverpakking brutogewicht	12,3 kg
Code geharmoniseerd systeem (HS)	84733020

Overige specificaties

Chipset	DisplayLink DL6950 VL813
---------	--------------------------



4250078166573

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date