



FOCUS PX



SPECIAL FEATURES

- ❖ Super-High Efficiency, 80 PLUS® Platinum Certified
- ❖ Fully Modular Cabling Design
- ❖ Compact Size (140 mm)
- ❖ 120 mm Fluid Dynamic Bearing (FDB) Fan
- ❖ Seasonic Hybrid Silent Fan Control
- ❖ Highly Reliable Japanese 105 °C Aluminum Electrolytic Capacitors
- ❖ Tight Voltage Regulation (12 V, 5 V and 3.3 V) [± 3%]
- ❖ Cable-free Connection Design
- ❖ Multi-GPU Technology Support

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
SSR-850PX	20 A	20 A	70 A	0.3 A	3 A	850 W
	100 W		840 W	3.6 W	15 W	
SSR-750PX	20 A	20 A	62 A	0.3 A	3 A	750 W
	100 W		744 W	3.6 W	15 W	
SSR-650PX	20 A	20 A	54 A	0.3 A	3 A	650 W
	100 W		648 W	3.6 W	15 W	
SSR-550PX	20 A	20 A	45 A	0.3 A	3 A	550 W
	100 W		540 W	3.6 W	15 W	



CONNECTOR QUANTITY

Model	Cable	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	Molex to SATA 3.3 Adapter
	SSR-850PX		1	2	6 (3 cables)	10	5
SSR-750PX		1	2	4 (2 cables)	10	3	2
SSR-650PX		1	2	4 (1 cables)	10	3	2
SSR-550PX		1	2	2 (1 cables)	10	3	2



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 140 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



Headquarters sales@seasonic.com
 USA ssa.sales@seasonic.com
 Europe sse.sales@seasonic.com